



TECHNICAL DATA SHEET

Lifebuoy Lights L160-L163

Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

Daniamant products cover 11 key areas:

- Lifejacket Lights
- Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
 - Special Lights
 - LED Flares
- Bridge Navigational Watch Alarm System (BNWAS)
 - Salinometers
 - Oil Level Alarm
 - Electronic Inclinator
- Agency for a range of world-renowned safety product brands (supplied to the Danish market)

| MODEL | L160 | L161 | L162 | L163 |
|--------------------------------------|---|--------------------------|------------------------|----------------|
| Part number | 62-001A | 62-002A | 62-003A | 62-004A |
| Colour – Light | Yellow | | International Orange | |
| Colour – Bracket | Black: Order 62-116 as Spare Part | | | |
| Light – Output | 2 Candela minimum | | | |
| Light – Duration | 2 hours min | 2 hours min | 15 hours min | 15 hours min |
| Light – Type | Flashing LED | | | |
| Material – Lifebuoy Light | Polypropylene Ether + PS | | | |
| Material – Bracket | Polypropylene | | | |
| Storage Temperature | -30° C to + 65° C | | | |
| Operating Temperature | -1° C to + 30° C | | | |
| Storage Life | 5 years | 5 years | 5 years | 5 years |
| Drop Height | 76 metres | | | |
| Weight – Nominal | 255 grams | 300 grams | 300 grams | 320 grams |
| Battery Type | Lithium Manganese Dioxide | | | |
| Activation | Automatic via Pull Cord | | | |
| Intrinsically Safe | No | Yes | No | Yes |
| Nato Stock number | 6230 99 613 4941 | 6230 99 366 5928 | - | - |
| Approvals – Classification Societies | SOLAS/MED | SOLAS/MED/ ATEX/IECEX | SOLAS/MED/ USCG/ETL | SOLAS/MED/USCG |
| Approvals – Country | See our web site for full list of Country approvals | | | |

Transport Specification

Transport Regulations are subject to change. Please refer to the latest Product safety Data Sheet at www.daniamant.com for details.

Packing Specification

To minimize shipping costs, all Lifebuoy Lights are packed in boxes 10 off.

The dimensions are;
Box of 10 off: 58 x 23 x 20 cm

Approximate packed weights are,
L160: 10 off at 3.7 kg.
L161: 10 off at 4.2 kg.
L162: 10 off at 4.2 kg.
L163: 10 off at 4.4 kg.

Daniamant Ltd
 Unit 3, The Admiral Park
 Airport Service Road
 Portsmouth, PO3 5RQ
 United Kingdom

Tel +44 23 92 67 51 00
 Fax +44 23 92 67 51 01
 sales@daniamant.com

Daniamant ApS
 Industrivej 24C
 3550 Slangerup
 Denmark

Tel +45 47 37 38 00
 Fax +45 47 37 38 09
 orders@daniamant.com

Daniamant Electronics A/S
 Industrivej 24C
 3550 Slangerup
 Denmark

Tel +45 47 37 38 00
 Fax +45 47 37 38 09
 info@daniamant.com

Outline

