



3C PROPOLYMER® HAZ-LO® ATEX RATED AND INTRINSICALLY SAFE LED FLASHLIGHT



- Material/Lens** Impact and chemical resistant Engineering Polymer resin; o-ring sealed and vented. Available in high visibility yellow or orange. Unbreakable polycarbonate lens with scratch resistant coating
- Dims/Weight** Length: 9.30 in. (23.62 cm); Body diameter: 1.46 in. (3.71 cm); Face cap diameter: 2.08 in. (5.28 cm); 6.8 oz (193 grams) without batteries; 13.9 oz (394 grams) with batteries (batteries sold separately)
- Light Source/ Output** White LED technology, shock-proof with a 50,000 hour lifetime. Smooth parabolic reflector produces a tight beam with optimum peripheral illumination. Regulated run time provides consistent performance throughout battery life. 120 lumens (high); runs 6.5 hours on low
- Switch** Push-button tail switch. Sealed switch design protects it from corrosion caused by battery leakage
- Battery** Three "C" alkaline batteries (sold separately)
- Features**
- High-performance, anti-static, thermoplastic material resistant to chemicals and solvents
 - Captured locking" set screw will not back out - prevents FOD (Foreign Object Debris)
 - Safety measure: Set screw helps to avoid batteries being changed out, or the housing inadvertently being opened in a hazardous environment
 - Set screw goes into a metal tray that evenly distributes pressure to protect the body from over-tightening of the set screw
 - Re-inforced pocket clip clamps securely to belts and gear
 - IP64/IPX7 rated; dust-tight, waterproof to 1m for 30 minutes
 - 3 meter impact resistance tested
 - Larger size makes the 3C ProPolymer HAZ-LO ideally suited for situations where gloves are typically worn
- Approvals**
- ATEX:**
ATEX-approved for Category 1 (Zone 0) locations
II 1G Ex ia IIC T4 Ga
II 1D Ex ia IIIC T99°
FTZU 11 ATEX 0183X
- InMetro:**
UL-BR 12.0516X Ex ia IIC T4 Ga; Ex ia IIIC T99°C
- MC-UL-US Classified Class I, Division 1, Groups A,B,C,D; Class II, Division 1, Groups E,F,G; Class III; Exia; Temperature Code T4
Most models meet applicable European Community Directives. MSHA Permissible Flashlight; Approval. No. 20-4140001-0: Tested for Intrinsic Safety in Methane-Air mixtures only. Charge or replace batteries in fresh air only
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Item	UPC	Part #
3C ProPolymer HAZ-LO - Yellow	080926-33820-3	33820
3C ProPolymer HAZ-LO - Orange	080926-33822-7	33822
3C ProPolymer HAZ-LO (InMetro) - Yellow	080926-33824-1	33824
3C ProPolymer HAZ-LO (InMetro) - Orange	080926-33825-8	33825
Lanyard with Push Button Slide*	080926-72024-4	72024
Holster	080926-25090-1	25090



*Not shown