

Quick Facts

Systems Include:

- Rocking Piston Compressor(s)
- Cabinet Option
- Diffuser Head(s)
- Weighted Tubing
 - Included as standard on 1-3 diffuser systems
 - Sold separately on 4-6 diffuser systems
- Designed for 24-hour operation with minimal maintenance
- Inlet air filter visual maintenance indicator
- Patent Pending noise cancelling design to dramatically reduce compressor sound

Compressor

Teich-Aire KM-120C

- 1/2HP, Oil-less piston compressor
- Continuous Duty Rated
- 115V (KM-120C) 4.0 amps @ 20 psi
- 230V (KM-120HC) 2.0 amps @ 20 psi
- 4.9 CFM @ 5 psi; 4.0 CFM @ 25 psi
- 25 psi pressure relief valve
- Ramped reed valve
- Heat resistant tubing
- Paper air filter element
- Can supply up to 3 diffuser heads

Teich-Aire KM-200C

- 3/4HP, Oil-less piston compressor
- Continuous Duty Rated
- 115V (KM-200C) 6.9 amps @ 20 psi
- 230V (KM-200HC) 3.7 amps @ 200 psi
- 7.2 CFM @ 5 psi; 6.2 CFM @ 25 psi
- 25 psi pressure relief valve
- Ramped reed valve
- Heat resistant tubing
- Paper air filter element
- Can supply up to 3 diffuser heads

Diffuser

- Independently tested to produce the most flow
- Self-weighted, stainless steel base
- Integrated tubing strain relief & rope tie-offs
- Molded plastic edge guards to protect pond lining
- Proprietary linear low-density polyethylene & rubber diffuser hose
- 23"x15.5" assembled
- Diffuser hose sits 6" above bottom of base
- Check valve

SureSink Weighted Tubing

- Available in 3/8" or 5/8" ID and 100' rolls or 500' reels
- Self-weighted
- 100' packages include all fittings
- 3/8" recommended up to 300' runs
- 5/8" recommended for greater than 300' runs

Cabinet Options

No Cabinet

- Galvanized Steel Mounting Bracket
- 16" on-center template
- 110 CFM, Cooling Fan with Guard
- Accommodates one ½ or ¾ HP compressor

Post Mount Cabinet

- Coated, aluminum, lockable cabinet
- Internal sound dampening foam
- Mounting template for 4x4 post or wall
- Hinged top & font cover for easy access
- 110 CFM cooling fan with guard
- 11.5"x11.4"x18.5"
- Accommodates one ½ HP compressor
- 6' pigtail with plug

Large Cabinet

- Coated, aluminum, lockable cabinet
- Recommended installing on ground pad
- Angled & hinged top cover for easy access
- 110 CFM cooling fan for each compressor
- 20.1"x17.1"x23.7"
- Accommodates one or two ½ or ¾ HP compressors
- 115V has 6' pigtail with plug

Optional Remote Manifold (RM)

- Valve box to house remote manifold
- PVC fittings and valves to position closer to pond edge

Warranty

- Compressor Motor 3 years
- Diffusers Lifetime
- Cabinet Lifetime
- SureSink Tubing 15 years



Model #	Compressor(s)	# of Diffusers	Cabinet	Voltage/ Phase/Hz	Running Amps	CFM @ 10psi	Number of Boxes
RA2DP-NC	KM-120C	2	No Cabinet	115V/1/60	3.5	4.8	5
RAH2DP-NC	KM-120HC	2	No Cabinet	230V/1/60	1.75	4.8	5
RA2DP-PM	KM-120C	2	Post Mount	115V/1/60	3.5	4.8	5
RAH2DP-PM	KM-120HC	2	Post Mount	230V/1/60	1.75	4.8	5
RA2DP	KM-120C	2	Large Cabinet	115V/1/60	3.5	4.8	5
RAH2DP	KM-120HC	2	Large Cabinet	230V/1/60	1.75	4.8	5
RA4DP	KM-120C (x2)	4	Large Cabinet	115V/1/60	7	9.6	5*
RAH4DP	KM-120HC (x2)	4	Large Cabinet	230V/1/60	3.5	9.6	5*
RA5DP	KM-120C (x2)	5	Large Cabinet	115V/1/60	7	9.6	6*
RAH5DP	KM-120HC (x2)	5	Large Cabinet	230V/1/60	3.5	9.6	6*

^{* -} Tubing not included

Model #	Compressor(s)	# of Diffusers	Cabinet	Voltage/ Phase/Hz	Running Amps	CFM @ 10psi	Number of Boxes
RA4XL	KM-200C (x2)	4	Large Cabinet	115V/1/60	12.3	13.6	5*
RAH4XL	KM-200HC (x2)	4	Large Cabinet	230V/1/60	6.2	13.6	5*
RA5XL	KM-200C (x2)	5	Large Cabinet	115V/1/60	12.3	13.6	6*
RAH5XL	KM-200HC (x2)	5	Large Cabinet	230V/1/60	6.2	13.6	6*
RA6XL	KM-200C (x2)	6	Large Cabinet	115V/1/60	12.3	13.6	7*
RAH6XL	KM-200HC (x2)	6	Large Cabinet	230V/1/60	6.2	13.6	7*

^{* -} Tubing not included

Depth (Ft.)	GPD per Diffuser (DP Systems)	GPD per Diffuser (XL Systems)
9	2,274,480	
12	3,411,720	
15	5,117,580	
18	6,652,854	
21	8,648,710	