



ENGINEERING & TECHNICAL DATA — Genesis® StatPath® Plus

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1	.14	N/A	2.5	N/A	29	18
1.25	.23	N/A	2.5	N/A	29	20
1.5	.28	N/A	3.25	N/A	29	18
2	.48	N/A	4.5	N/A	29	15

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Light weight polyethylene conductive copolymer hose with a yellow skimcoat reinforced with an integral polyethylene helix

Temperature Range: -40°F to 140°F

Standard Color: Black with Yellow Skimcoat

Standard Lengths: 25 & 50 Feet

- Surface Resistivity Level: 10^3 - 10^5 Ohms/Square

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

