



ENGINEERING & TECHNICAL DATA — Heat-Flex® GS

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
.75	.08	N/A	1	3:1	29	30
1	.12	N/A	1.2	3:1	29	30
1.5	.17	N/A	1.8	3.7:1	29	30
1.75	.21	N/A	1.9	3.7:1	29	30
2	.25	N/A	2	3.7:1	29	30
2.5	.3	N/A	2.3	3.7:1	29	30
3	.33	N/A	2.5	3.7:1	29	30
3.5	.4	N/A	2.5	3.7:1	29	30
4	.48	N/A	3	4.8:1	27	30
4.5	.54	N/A	3.2	4.8:1	20	30
5	.59	N/A	3.5	4.8:1	14	30
6	.62	N/A	4	6:1	9	19
8	.79	N/A	4	6:1	9	14
10	.98	N/A	5	6:1	1	11
12	1.2	N/A	5	6:1	.6	9.4

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Double-ply silicone coated fiberglass fabric hose reinforced with a spring steel wire helix & external filament fiberglass cord

Temperature Range: -65°F to 550°F, Intermittent to 600°F

Standard Color: Iron Oxide Red

Standard Lengths: 12 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

