



ENGINEERING & TECHNICAL DATA — Dayflex[®] Saniflex[®]

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
.75	.07	N/A	.75	1.5:1	29	30
1	.09	N/A	1	1.5:1	29	30
1.25	.13	N/A	1.25	2:1	29	28
1.375	.14	N/A	1.4	2:1	20	28
1.5	.16	N/A	1.75	2:1	20	20
1.625	.18	N/A	2	2:1	20	20
2	.23	N/A	2	2:1	10	18

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Plastic helix supported PVC tape hose

Temperature Range: -20°F to 180°F

Standard Color: Natural

Standard Lengths: 50 Feet

- Meets IAPMO compliance

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

