

NEW PRODUCTS!

LUG-ALL®
WEB STRAP RATCHET WINCH HOISTS

1-1/2 TON SMALL FRAME

2 TON SMALL FRAME

Standard Version
With eye bolt and third hook



Convertible Version
With bracket that eliminates need for third hook



LIGHTWEIGHT MODELS

We know that in the field, you want light, compact, and strong tools for the efficient pulling of electric lines. That's why we designed our newest web strap pullers to be the lightest, most compact ones ever.

Models 35 (1-1/2 ton) and 40 (2 ton) are available as both convertible or standard hoists. Like all LUG-ALL Lineman's Hoists, these new models meet rigorous ANSI/ASME B30.21 standards.



MODEL #	CAPACITY	DOUBLE PULL DISTANCE		CAPACITY	SINGLE PULL DISTANCE		STRAP LENGTH	HANDLE LENGTH	NET WEIGHT (LBS.)
		Min	Max		Min	Max			
35-A	1-1/2 Ton	27"	7'-2"	3/4 Ton	19"	15'-4"	16'	30"	12.75
35-B	1-1/2 Ton	27"	7'-2"	3/4 Ton	19"	15'-4"	16'	32"	13
35-U	1-1/2 Ton	30"	7'-1"	3/4 Ton	21"	15'-4"	16'	30"	13.25
35-UB	1-1/2 Ton	30"	7'-1"	3/4 Ton	21"	15'-4"	16'	32"	13.25
35-HB	1-1/2 Ton	29"	7'-1"	3/4 Ton	20"	15'-4"	16'	32"	13.25
40-A	2 Ton	25"	4'-1"	1 Ton	19"	9'-4"	10'	36"	13.25
40-B	2 Ton	25"	4'-1"	1 Ton	19"	9'-4"	10'	38"	13.5
40-U	2 Ton	29"	4'-0"	1 Ton	21"	9'-4"	10'	36"	13.75
40-UB	2 Ton	29"	4'-0"	1 Ton	21"	9'-4"	10'	38"	13.75
40-HB	2 Ton	27"	4'-0"	1 Ton	20"	9'-4"	10'	38"	13.75
35-CA	1-1/2 Ton	19"	7'-6"	3/4 Ton	19"	15'-2"	16'	30"	12
35-CB	1-1/2 Ton	19"	7'-6"	3/4 Ton	19"	15'-2"	16'	32"	12.25
35-CU	1-1/2 Ton	21"	7'-5"	3/4 Ton	21"	15'-2"	16'	30"	12.5
35-CUB	1-1/2 Ton	21"	7'-5"	3/4 Ton	21"	15'-2"	16'	32"	12.5
35-CHB	1-1/2 Ton	21"	7'-5"	3/4 Ton	21"	15'-2"	16'	32"	12.5
40-CA	2 Ton	19"	4'-5"	1 Ton	19"	9'-2"	10'	36"	12.5
40-CB	2 Ton	19"	4'-5"	1 Ton	19"	9'-2"	10'	38"	12.75
40-CU	2 Ton	21"	4'-4"	1 Ton	21"	9'-2"	10'	36"	13
40-CUB	2 Ton	21"	4'-4"	1 Ton	21"	9'-2"	10'	38"	13
40-CHB	2 Ton	21"	4'-4"	1 Ton	21"	9'-2"	10'	38"	13

5 HOOK STYLES

- A** - Standard Latching Hooks
- B** - Hot Stick Rings and Latching Hooks
- U** - Gate Type Hooks
- UB** - Gate Type Hooks and Hot Stick Rings
- HB** - Hot Stick Rings and Hook Latches

MODEL DESIGN

- C** - Convertible Model

*All models equipped with quick release pulley block*LUG-ALL grips, straps, and hooks are color coded by capacity*

Specifications are subject to change without notice

WARNING

LUG-ALL web strap hoists are NOT insulating live-line tools. When the hoist's strap is clean and dry, it may have dielectric properties typical of nylon or polyester fibers; however, when it becomes wet and/or dirty, the strap loses these dielectric properties.

Use appropriate insulating hot sticks in series with web strap hoist hot-stick rings when necessary to achieve proper working distance per OSHA Regulation Subpart V, 1926.950 or company work practices. When the hoist handle swings closer to an energized conductor than OSHA working distances or company work practices permit, use rubber gloves rated for appropriate voltage.

TO AVOID PERSONAL INJURY OR EQUIPMENT DAMAGE

- Do not use if web strap is twisted, kinked, frayed, or damaged.
- Do not use to lift people, or loads over people.
- Do not leave an unattended load suspended in the air.
- Do not lengthen, or make any substitution for the LUG-ALL reversible handle.
- Do not remove or obscure warning labels.
- Do not use hoist as a load binder.
- Do not snag or pull the strap over edges, as serious weakening may result.
- Do not use a LUG-ALL hoist as a tow line.
- Close latches on hook before using.
- Use only LUG-ALL replacement parts.

The use of the web strap hoist on or around energized lines may result in serious injury or death.



RAPID, CONTINUOUS, CUSTOMER-DRIVEN IMPROVEMENTS

Your professional feedback drives our process of rapid, continuous improvements of our hoist designs. Our world-class manufacturing facilities enable us to take your suggestions from the field and manufacture them in as soon as a week.

And our team culture — deeply rooted and nurtured by 3rd generation owners and workers — allows us to consistently deliver unmatched quality, operation and durability in every hoist we make.

LUG-ALL®...Raise Your Expectations™

WARRANTIES, PARTS & REPAIRS

We guarantee that your LUG-ALL hoist is free from defects in material and workmanship for one year from your date of purchase. In addition to a comprehensive online Parts Store at LUG-ALL.com, we also offer factory repairs and reconditioning. We want you to be satisfied for the life of your hoist!

LUG-ALL®
WEB STRAP RATCHET WINCH HOISTS

For inquires, call us at:
877-658-4255 toll free

650 Lincoln Road
Birdsboro, PA 19508

Local: 610-286-9884
Fax: 610-286-9661
Web: lug-all.com
Email: sales@lug-all.com

