



RKI Instruments

Calibration Station for GX-2009; 81-SDM2009-06

Pine Item #17946

DESCRIPTION:

Stand Alone Station

The SDM-2009 is a versatile maintenance tool that automates the service of a GX-2009 portable gas monitor. This docking station can be used as a stand alone device for charging, calibration and bump testing, with all records stored automatically for future upload to a PC via USB flash drive (PC software and flash drive included).

Multi Module System

Automate how you manage and service GX-2009 instruments by connecting the SDM-2009 to a computer with a USB cable. With the SDM Docking Station controller software, you can simultaneously calibrate, bump test, archive data, or charge up to ten instruments. Also, download the datalogging history from each instrument into one easy to manage locator. SDM-2009 stations can be manifolded together to reduce the number of demand flow regulator gas cylinders required.

FEATURES:

Stand Alone Station

- Stand-alone station (no PC Required)
- Charging
- Calibration
- Bump Test
- Save Bump Test and Calibration records
- Bump test and calibration records copy to USB jump drive
- Includes PC software for viewing/archiving bump test and calibration records

Multi Module System

- Multiple modules connected to a PC (10 max)
- Charging
- Calibration
- Bump Test
- Automatic calibration/bump test option
- Configure GX-2009 parameters
- Archive Bump Test and Calibration records
- Archive data to network location
- Software controlled data retrieval
- Windows 7 compatible

Contact a Pine branch near you to request a quote or place an order

VISIT OUR U.S. AND CANADA WEBSITES TO FIND A BRANCH NEAR YOU

United States

www.pine-environmental.com

Canada

www.pine-environmental.ca

Product Specifications

Input Power	12 VDC NOTE: AC Adapter with 100 - 240 VAC, 50/60 Hz, 0.6A input and 12 VDC, 1.2A output provided as standard.
Environmental Conditions	<ul style="list-style-type: none"> • For Indoor Use Only • -10° C to 40° C, below 80% Relative Humidity, Non-Condensing
Applicable Instruments	GX-2009
Maximum Number of Records Saved	200 (stand-alone). Unlimited with software
3 Ports	1 Calibration gas, 1 fresh air and 1 exhaust
Standard Accessories	<ul style="list-style-type: none"> • AC Adapter • USB Flash Drive • Single Module Data Viewer Software • SDM GX Docking Station PC Controller Program • Inlet Air Filter • Instruction Manual • 10 Foot Long Exhaust Tube • One 3 Foot Long Tube for GAS Fitting • 2 T-Fittings (for PC Controlled Configuration only) • 10 Foot Long 3/16 Inch Tube for GAS manifolding (used for PC Controlled Configuration only) • Check Valve (used for PC Controlled Configuration only) • USB Cable, Type A to Type B




Local Delivery Pick-up



In-Stock Equipment



Repair & Calibration



Rental Protection Plan