

Ludlum

Ludlum Model 3 (With 44-9 or 44-38 Detector)

Pine Item #51516

DESCRIPTION:

This is Ludlum's best selling, general purpose, handheld analog ratemeter known for accuracy and long-lasting dependability. The analog meter comes in a variety of measurement ranges and units to support the external radiation detector selected.

The aluminum cast instrument housing with its separate battery compartment and accompanying metal handle offer an industrial robustness and quality that promote long-lasting protection and instrument life. The front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, battery test, an audio on/off switch, a fast/slow response switch, and a count reset button.

FEATURES:

- Rugged
- 4-Decade Analog Ratemeter
- Supports GM & Scintillation Type Detectors
- Greater than 2000 Hour Battery Life



Contact a Pine branch near you to request a quote or place an order

VISIT OUR U.S. AND CANADA WEBSITES TO FIND A BRANCH NEAR YOU

United States

www.pine-environmental.com

Canada

www.pine-environmental.ca

Product Specifications

Application:	alpha beta and gamma surveying
Detection Range:	typically 0-200 mR/hr or 0-500000 cpm
Compatible Detectors:	GM scintillation
Linearity:	reading within 10% of true value with detector connected
High Voltage:	adjustable from 400-1500 Vdc
Threshold:	fixed at 40 mV




Local Delivery Pick-up



In-Stock Equipment



Repair & Calibration



Rental Protection Plan