

Aeroqual

Indoor Air Quality Test Kit for WELL Building Standard

Pine Item #52269

DESCRIPTION:

Coronavirus / COVID-19 FEATURED ITEM!

The Indoor Air Quality Test Kit for WELL is for consultants and air quality professionals who require a set of tools to measure indoor pollutants designated by the Air Concept for IWBI's **WELL Building Standard™ (WELL)**.

The Kit features Aeroqual's proven Series 500 portable monitor that can be used to measure a range of WELL designated pollutants by simply swapping the sensor heads for the pollutant you wish to monitor. The kit includes the following sensors: a particulate matter (PM) sensor (PM2.5/PM10), two indoor pollutant gas sensors (O3, CO), and a combined temperature and relative humidity sensor.

FEATURES:

- Series 500 Monitor base including: LCD digital display, Lithium battery and charger, in-built datalogger, monitor to USB cable, PC software.
- Particulate Matter Sensor PM10 / PM2.5
- Carbon Monoxide Sensor 0-100ppm
- Ozone Sensor 0-0.5ppm
- Temperature & Humidity Sensor
- Small Carry Case

APPLICATIONS:

- WELL Compliance assessments
- Personal exposure checks
- Health and safety compliance
- Checking indoor air pollution "hotspots"

For more information on WELL Health-Safety Rating, please visit <https://www.wellcertified.com/#>



STEP 1. Gather data



STEP 2. Download data



STEP 2. Analyze data

Contact a Pine branch near you to request a quote or place an order

VISIT OUR U.S. AND CANADA WEBSITES TO FIND A BRANCH NEAR YOU

United States

www.pine-environmental.com

Canada

www.pine-environmental.ca

SENSOR SPECIFICATIONS:

GAS & PARTICULATE SENSORS	RANGE	SENSOR TYPE*	MINIMUM DETECTION LIMIT	ACCURACY OF FACTORY CALIBRATION	RESOLUTION	RESPONSE TIME	TEMPERATURE	RELATIVE HUMIDITY	KIT		
									STR	PRO	WELL
Particulate Matter (PM ₁₀ & PM _{2.5})	0.000 to 1.000 mg/m ³	LPC	0.001 mg/m ³	± (0.002 mg/m ³ + 15 % of reading)	0.001 mg/m ³	5 Seconds	0 to 40°C	0 to 90 %	✓	✓	✓
Ozone (O ₃)	0-0.5ppm	GSS	0.001ppm	<±0.008ppm 0-0.1 ppm <±10% 0.1-0.5 ppm	0.001ppm	60 Seconds	0 to 40°C	10 to 90%			✓
Carbon Dioxide (CO ₂)	0-5000 ppm	NDIR	20 ppm	<±20ppm + 5%	1 ppm	120 Seconds	0 to 40°C	15 to 90%	✓	✓	
Carbon Monoxide (CO)	0-100ppm	GSE	0.2ppm	<±1ppm 0-10 ppm <±1 10% 10-100 ppm	0.01ppm	30 Seconds	0 to 40°C	15 to 90%		✓	✓
VOC	0-25 ppm	GSS	0.1 ppm	<±0.1 ppm + 10%	0.1ppm	60 Seconds	0 to 40 °C	15 to 90%	✓		
VOC	0-20ppm	PID	0.01ppm	<±0.2ppm + 10%	0.01ppm	30 Seconds	0 to 40°C	0 to 95%		✓	

* **Sensor Types:** Gas Sensitive Semiconductor (GSS), Gas Sensitive Electrochemical (GSE), Laser Particle Counter (LPC), Non-dispersive infrared (NDIR), Photoionization Detector (PID).

For the full range of available sensors, visit our website; www.aeroqual.com or to download the list, click here.

MONITOR SPECIFICATIONS:

SERIES 500 PORTABLE MONITOR SYSTEM SPECIFICATIONS (included in Starter & Pro Air Testing Kits)	
Measurement units	Gas: ppm or mg/m ³ Humidity: % Temperature °C or F
Reading functions	Instant, minimum, maximum, average
Sensor head	Active fan sampling to ensure high accuracy measurements, interchangeable, replaceable
Display status indicators	Battery, sensor, standby
Sensor calibration	Zero and gain calibration in the lab or field
Analog output	0-5 V
Digital interface	RS-232 to USB
Data logging	Up to 8,188 records(2,706 incl. Temp/RH)
PC data logging	Software and data cable supplied. Link data to a specific location and monitor.
Clock function	Real time
Power supply	12V DC (power adaptor/charger supplied 100-250 V AC)
Rechargeable battery	Lithium polymer 12 V DC 2700 mA/h
Enclosure material and rating	PC and ABS; IP20 and NEMA 1 equivalent
Size	(L x W x D) 195 x 122 x 54 (mm); 7 x 4¾ x 2 (in) (with sensor head)
Weight	< 460 g; < 16 oz(with sensor head and battery)
Environmental operating conditions	Temperature: -5 °C to 45 °C Humidity: 0 to 95 % non-condensing
Temperature & Humidity sensor	Range - 40 °C to 124 °C (- 40 °F to 255 °F); Range 0 to 100 % RH
Approvals	Part 15 of FCC Rules; EN 50082-1: 1997; EN 50081-1: 1992




Local Delivery Pick-up



In-Stock Equipment



Repair & Calibration



Rental Protection Plan