



Partner for Test & Measurement
Equipment Services and Data Solutions

Pushrod & Well Cameras

Remote Visual Inspection (RVI)

Laval Underground Surveys

Laval SC-350 Inspection Camera & SC350/500 9" Monitor

Pine Item #55657

DESCRIPTION:

The SC-350 is an ultra-light, compact, camera system with the SC-166 water well camera designed for water wells, boreholes, and vertical shafts as small as 2 inches (5 cm) to 10 inches (25 cm) in diameter. Additional lighting accessories are available to expand the viewing capabilities. The winch is manually operated with a collapsible handle to make it completely compact, portable and easily shippable. The brake lever allows the user to stop the reel at any point for a thorough inspection.

The system comes standard with the winch, control center, monitor, SC-166 Camera, and power cable. The SC-350 is also compatible with Laval's R-Cam line of equipment which allows the option to upgrade to an R-Cam System or complement their existing R-Cam.

FEATURES:

- Ultra-Light, Compact and Portable
- Survey Water Wells, Boreholes, and Vertical Shafts from 2 inches (5 cm) to 10 inches (25 cm)
- Manually Operated Winch with Collapsible Handle
- Braking System allows 360 degree Stopping Capability
- Standard System Includes: Winch, Control Center, Monitor, Camera, and Power Cable
- Completely Compatible with R-Cam Product Series, easily upgrade the system or compliment an existing R-Cam
- Full Line of SC-350 Accessories including DepthCounter Tripod Assembly Available



Contact a Pine branch near you to request a quote or place an order

VISIT OUR U.S. AND CANADA WEBSITES TO FIND A BRANCH NEAR YOU

United States

www.pine-environmental.com

Canada

www.pine-environmental.ca

Product Specifications

Cable	350 feet (107 meters) or 500 feet (152 meters) of Kevlar Reinforced Coaxial Cable
Cable Head	Detachable Laval Quick-Connect Cable Head, Pressure Rated to 5,000 PSI with Built in Strain Relief
Drive	Manual Hand Crank Reel with Collapsible Handle for Maximum Portability
Power Supply	12VDC Power Cable. Optional 12V Battery Pack or 120VAC/220VAC Adaptor
Brake	Interlocking, Manual Brake with Actuator Lever for 360 degree Stopping Capability
Dimensions	17 Inches High (43 cm), 15.5 inches Wide (40 cm), 15 inches Deep (39 cm)
Weight	22 lbs (10 kg) without cable. 30 lbs (13.6 kg) with 350 feet (107 m) and 33 lbs (15 kg) with 500 feet (152 m)
Monitor	7 inch LCD Color Monitor with Adjustable Mounting Bracket
Depth Counter	Encoder Ready, On-screen Depth Display measured in feet and tenths or meters with Optional Tripo



Local Delivery Pick-up



In-Stock Equipment



Repair & Calibration



Rental Protection Plan

Video:
<https://youtu.be/qMfebNg-pNZs>