

Model 192 MicroR Ratemeter



Ludlum Measurements, Inc.

Features

- High Sensitivity to Gamma
- Range: 0 to 50 $\mu\text{Sv/h}$ (0 to 5000 $\mu\text{R/hr}$)
- Rugged
- 4-Range Analog Meter
- Setpoint and Deviation Alarms
- Adjustable Audio & Visual Alarms



Introduction

The Model 192 is a high-sensitivity gamma $\mu\text{R}/\text{meter}$ employing an internally housed 5.1 cm diameter by 2.5 cm thick (2 x 1 in.) NaI(Tl) detector.

This instrument supports two types of alarms: a user adjustable fixed point alarm and a deviation alarm that activates at levels above a floating background. An alarm light mounted to the front panel is accompanied by an audio signal when alarm setpoints are passed.

The front-panel controls include a rotary switch for selecting one of four ranges, instrument shut-off and battery test, an audio on/off switch, a fast/slow response switch, and a reset button. The aluminum cast instrument housing with its separate battery compartment and accompanying metal handle offer an industrial robustness and quality that promote long-lasting protection and instrument life. The Model 192 is a complete turn-key system and includes two "D" cell batteries.

Specifications

Part Number: 48-2945

APPLICATION: low-level (microR) gamma survey

RANGE: 0 to 50 $\mu\text{Sv/h}$ (0 to 5000 $\mu\text{R/hr}$)

DETECTOR: 5.1 cm diameter x 2.5 cm thick (2.0 x 1.0 in.) NaI(Tl) scintillator

SENSITIVITY: typically 65,000 cpm/ $\mu\text{Sv/h}$ (650 cpm/ $\mu\text{R/hr}$) (^{137}Cs gamma)

ENERGY RESPONSE: energy dependent

LINEARITY: reading within 10% of true value

METER: 6.4 cm (2.5 in.) arc, 1 mA analog type, pivot and jewel suspension

METER DIAL: 0 to 5 $\mu\text{R/hr}$, BAT TEST (others available)

ALARMS: This instrument incorporates dual action, latching type alarms:

- A fixed alarm point that can be set at any point from 10% of full scale to full scale, and is indicated by a constant audible tone and the lamp turning on.
- A quick deviation alarm that is based on background radiation levels. When the instrument is turned on, it takes an eight-second measurement of background radiation levels and determines a deviation alarm setting. If the radiation level exceeds this setting, the alarm audio will beep every 1/8 second and the lamp will flash.

CONTROLS:

- Rotary Selector: switches between instrument off, battery check, ranges: x1, x10, x100, x1000
- Response Switch: toggles between FAST (4 seconds) or SLOW (22 seconds) from 10% to 90% of final reading
- Reset Pushbutton: to zero meter, and also re-accumulate background data and recalculate the alarm point
- Audio Switch: for audio on/off, built-in unimorph speaker, greater than 60 dB at 0.6 meters (2 ft)
- Calibration Controls: accessible from front of instrument (protective cover provided)

BATTERY LIFE: typically 600 hours with alkaline batteries (battery condition can be checked on meter)

SIZE: 21.6 x 8.9 x 22.4 cm (8.5 x 3.5 x 8.8 in.) (H x W x D), with handle

WEIGHT: 2.3 kg (5 lb) including batteries



Ludlum Measurements, Inc. P.O. Box 810, Sweetwater, Texas 79556

Web: <http://www.ludlums.com> Tel: 800-622-0828 / 325-235-5494 / Fax: 325-235-4672 / Email: sales@ludlums.com

Note: specifications subject to change without notification. We are not responsible for errors or omissions.

May 2015