



Temp Range -40°C to +90°C

A medium weight Polyurethane ducting with a copper-plated steel spiral sheathed in a blue PVC, for suction and transport of dusts, chips and abrasive materials.

	Ø I.D	Ø I.D	Wall Thickness	Weight	Bending Radius	W.P	Vacuum	Max Coil Length
Part No	Inch	mm	mm	kg/m	mm	Bar	mh2o	Mtr
RBL660-038	11/2	38	0.55	0.23	45	1.5	4.8	20
RBL660-051	2	51	0.55	0.29	60	1.2	3.5	30
RBL660-063	2 1/2	63	0.55	0.34	70	0.9	2.5	20
RBL660-076	3	76	0.65	0.47	85	0.8	2.0	30
RBL660-082	3 1/4	82	0.65	0.51	90	0.7	2.0	30
RBL660-090	3 1/2	90	0.65	0.53	100	0.7	2.0	20
RBL660-102	4	102	0.65	0.62	110	0.6	1.5	30
RBL660-110		110	0.65	0.65	120	0.6	1.5	20
RBL660-120		120	0.70	0.90	130	0.6	1.5	20
RBL660-127	5	127	0.70	0.95	135	0.5	1.5	30
RBL660-140	5 1/2	140	0.70	1.05	150	0.5	1.5	30
RBL660-152	6	152	0.70	1.15	160	0.4	1.0	30
RBL660-160		160	0.70	1.20	170	0.4	1.0	30
RBL660-180		180	0.70	1.35	190	0.4	1.0	20
RBL660-203	8	203	0.80	1.60	220	0.3	1.0	20
RBL660-229	9	229	0.80	1.80	240	0.3	0.5	20
RBL660-254	10	254	0.80	2.00	270	0.2	0.5	12
RBL660-305	12	305	0.80	2.40	320	0.2	0.4	10
RBL660-315		315	0.80	2.48	330	0.2	0.4	10

All technical specifications apply to a temperature of 23 °C ± 2°C – Tolerance on all specifications ± 5%