

# KVDA Split Strap KVDD Legs for Split Strap

Item No.	Ø mm	Thickness (T) mm	Width (b)	Bolts
KVDA-080	81,5	2,5	28	M8
KVDA-100	101,5			
KVDA-120	121,5			
KVDA-125	126,5			
KVDA-140	141,5			
KVDA-150	151,5			
KVDA-160	161,5			
KVDA-180	181,5			
KVDA-200	201,5			
KVDA-225	226,5			
KVDA-250	251,5			
KVDA-300	301,5			
KVDA-315	316,5			
KVDA-350	351,5			
KVDA-400	401,5			
KVDA-450	451,5			
KVDA-500	501,5			

Item No.	(L) mm	Thickness (T) mm	Width (b)	Bolts
KVDD <sub>F</sub> -080 - 160	65	2,5	40	M8
KVDD <sub>F</sub> -180 - 315				

Item No.	(L) mm	Thickness (T) mm	Width (b)	Bolts
KVDD <sub>L</sub> -080 - 160	235	3,0	40	M8
KVDD <sub>L</sub> -180 - 315	260			

Temperature Rating of Product Components	
° C	<b>KVDA Split Strap KVDD Legs for Split Strap</b>
-20°	Galvanised Steel
121°	
200°	

**Additional Notes**

At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 200° C.

