

Standard QF Clip


Ø mm	Weight kg
80	0,05
100	0,05
125	0,07
140	0,07
150	0,08
160	0,08
180	0,16
200	0,18
224	0,24
250	0,27
300	0,40
315	0,44
350	0,49
400	0,56
450	0,62
500	0,69
560	0,78
630	0,90
710	1,00

Heavy-Duty QF Clip

Ø mm	Weight kg
80	0,11
100	0,12
125	0,14
140	0,15
150	0,19
160	0,24
180	0,27
200	0,28
224	0,30
250	0,32
300	0,59
315	0,63
350	0,69
400	0,72
450	0,81
500	0,87
560	0,93
630	1,00
710	1,14




Standard QF Clip




See Right for Detail

Seal will be installed and folded over at the factory



Position # 1

While clamping down, slowly tuck extra seal underneath the opposing side of clip



Position # 2

Heavy-Duty QF Clip



Temperature Rating of Product Components

° C	QF Clip	Sealing	
200°	Galvanised Steel	Nitrile	Optional - Silicone
70° (intermittent to 90°)			
-20°			
-40°			
-54°			

Compliance / Rating of Product Components

Product	Material	Compliance / Rating
QF Clip	Galvanised	DX51D with Z275 Coating
Sealing	Nitrile	ASTM D 1056
	Silicone	ASTM-D-2000 M1GE605 – ZZ-R-765 Class 2 Grade 50 – AMS-3302