

# Material Safety Data Sheet

## **DIOSHY® TPE** Material Safety Data Sheet

Visit our Website at <http://www.dioshy.com>

### Section 1. Material / Company Identification

**PRODUCT NAME :** DIOSHY®TPE Series Products:

**CHEMICAL NAME :** Thermoplastic Elastomer Compound ( based on Styrene Block Copolymer ).

**PRODUCT FAMILY :** Thermoplastic Elastomer

**CORPORATE OFFICE**

DIOSHY CO., LTD.

NO.9, LANE 209, YUNG FENG RD., TAIPING CITY, TAIWAN, R.O.C

General Assistance : +886-4-22777389

Fax: +886-4-22776977

### Section 2. Hazards Identification

**Human Health Hazards**

Molten product adheres to the skin and causes burns.

**Safety Hazards**

Electrostatic charges may be generated during handling. Risk of self-ignition of bulk product above certain temperature (Refer to Section 10). Specifically for powder grades and accumulated polymer dust: dust explosion could occur.

**Environmental Hazards**

No specific Hazards

**Other Hazards**

Not classified as dangerous for supply or conveyance.

**Special Notes**

These materials are rubber compounds, which are essentially non-toxic. Material is not irritating. If polymer dusts are generated, they could scratch the eyes and cause minor irritation to the respiratory tract.

### Section 3. First Aid Measures

#### Symptoms and Effects

Not expected to give rise to an acute hazard under normal conditions of use.

#### Inhalation

Remove to fresh air. If rapid recovery does not occur, obtain medical attention.

#### Skin

If contact with hot material, cool the burn area by flushing with large amounts of water. DO NOT attempt to remove anything from the burn area or apply burn creams or ointments. Cover the burn area loosely with a sterile dressing, if available and seek medical attention.

#### Eye

Flush eye with water. Seek medical attention if necessary.

#### Ingestion

No specific measures.

#### Advice to physicians

Treat Symptomatically

### Section 4. Fire Fighting Measures

#### Specific Hazards

Not classified as flammable but will burn. Hazardous combustion products may include carbon monoxide, carbon dioxide.

#### Extinguishing Media

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

#### Unsuitable Extinguishing Media

Water in a jet may disperse fire.

#### Protective Equipment

Full protective clothing and self contained breathing apparatus.

### Section 5. Accidental Release Measures

#### Personal Precautions

Avoid raising a dust cloud

#### Environmental Precautions

No Specific Measures.

#### Clean-Up Methods - Small Spillage

Shovel up and place in a labeled, sealable container for subsequent safe disposal as required by local, state, federal, international or country specific regulations.

#### Clean-Up Methods - Large Spillage

Transfer to a labeled, sealable container for product recovery or safe disposal as required by local, state, federal, international or country specific regulations.

#### Protective Measures

Wear appropriate personal protective equipment (refer to Section 8) when responding to spills.

#### Spill Management

Shovel and sweep up or use industrial vacuum cleaner. Proper disposal should be evaluated based on regulatory status of this material (refer to Section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area. Prevent entry into waterways, sewer, or confined areas.

## Section 6. Handling and Storage

### Handling

Avoid generation or accumulation of dusts. Take precautionary measures against static discharges, earth/ground all equipment. Avoid contact with heated or molten product. Do not breathe dust. Do not breathe fumes or vapors from heated product. Use local exhaust extraction over processing area.

When processing DIOSHY®TPE products, maintain a fire watch if the material reaches 225 deg. C (437 deg. F) for LP Series · EP Series · MP Series · AB Series · PC Series · NL Series · HG Series · FG Series (polymers and compounds), and 280 deg. C (536 deg. F) for HP Series · GP Series (polymers and compounds).

The temperatures listed above are indicated only for safety reasons (risk of fire and product degradation) and are not necessarily recommended for processing.

Degradation of the polymer (polymer breakdown) will start at lower temperatures depending on the specific processing conditions. Therefore, operating below these temperatures does not guarantee the absence of product degradation.

For more information about processing precautions, consult the DIOSHY®TPE technical literature available from your sales representative.

Static charge buildup can be a potential fire hazard when used in the presence of volatile or flammable vapors or in high airborne dust concentrations. For more information, consult the DIOSHY®TPE Static Electricity Safety Bulletin available from your sales representative.

### Storage

Keep container dry. Keep in a cool, well-ventilated place. Keep away from direct sunlight and other sources of heat or ignition. Avoid storage of bulk product at temperatures above ambient to minimize risk of exothermic degradation, self-heating and possible self-ignition (Refer to Section 10). Avoid storage under pressure or at elevated temperatures to minimize particulate clustering. Do not stack Flexible Intermediate Bulk Containers (FIBCs) nor palletized bags.

### Storage Temperatures

Ambient

### Product Transfer

Take precautionary measures against static discharge. Earth/Ground all equipment.

### Other Information

DIOSHY®TPE has a tendency to accumulate static charge during transport, handling and processing. Reducing the velocity of transport will reduce charging. Static charge buildup can be a potential fire hazard when used in the presence of volatile or flammable mixtures. For more information, consult the DIOSHY®TPE Static Electricity Safety Bulletin available from your sales representative.

## Section 7. Exposure Controls / Personal Protection

### Occupational Exposure

None established. In the absence of occupational exposure standards for this product, it is recommended that the following be adopted:

#### RUBBER FUME

##### TLV (EH40)

#### RUBBER MANUFACTURING AND PROCESSING GIVING RISE TO RUBBER DUST AND RUBBER FUME

##### Rubber Fume

MEL/TWA (8 h) = 0.6 mg/m<sup>3</sup>

##### Rubber Process Dust

MEL/TWA (8 h) = 6 mg/m<sup>3</sup>

MEL = Maximum Exposure Limit

#### DUST, RESPIRABLE DUST

##### TLV (EH40)

##### Total Inhalable Dust

TWA (8 h) = 10 mg/m<sup>3</sup>

##### Respirable Dust

TWA (8 h) = 4 mg/m<sup>3</sup>

### Engineering Control Measures

Use local exhaust ventilation.

### Respiratory Protection

Where local exhaust ventilation is not practicable and odors are detected use a negative pressure half face respirator equipped with a cartridge designed to protect against organic vapors and if dust is also present a particulate pre-filter should also be used. For high airborne dust concentrations use a cartridge designed to be used against nuisance dust.

### Hand Protection

Cloth gloves if desired.

### Eye Protection

Dust-tight mono goggles.

### Body Protection

Standard issue work clothes which may include apron, safety shoes or boots as necessary.

## Section 8. Physical and Chemical Properties

**Physical State:** Solid

**Color:** White

**Odor:** Essentially odorless

**Flash Point:** Not applicable

**Density:** Typical between 880-950 kg/m<sup>3</sup> at 20C

**Specific Gravity:** <1

**Bulk density (for solids):** Typical 300-400 kg/m<sup>3</sup> at 20 Deg. C (ASTM D-1895)

**Solubility (In Water):** Insoluble

**N-octanol/water partition coefficient (log Pow):** Not applicable

## Section 9. Reactivity and Stability

### Stability

Stable under ambient conditions. Oxidizes exothermically above ambient temperature.

### Conditions to Avoid

Avoid contact with strong oxidizing agents. Accumulation of product in areas exposed to elevated temperatures for extended periods in air may result in self-heating and auto ignition. Avoid elevated temperatures in storage for prolonged periods of time (example: 5 days at 200 Degrees F or 93 Degrees C).

### Hazardous Decomposition Products

Hazardous vapors from heated products are not expected to be generated under normal processing temperatures and conditions. Although highly dependent on temperature and environmental conditions, a variety of thermal decomposition products may be present if the product is over heated, is smoldering or catches fire. These range from simply hydrocarbons (such as methane and propane) to toxic/irritating vapors (such as carbon monoxide and dioxide, acrolein, aldehydes and ketones). (Refer to Handling in Section 7).

## Section 10. Toxicological Information

### Basis for Assessment

Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the toxicology of similar products.

### Acute Toxicity Oral

Expected to be of low toxicity, LD50 > 2000 mg/kg

### Acute Toxicity Dermal

Expected to be of low toxicity, LD50 > 2000 mg/kg

**Acute Toxicity Inhalation**

Data not available.

**Skin Irritation**

Not expected to be irritating.

**Eye Irritation**

Not expected to be irritating.

**Skin Sensitization**

Not expected to be a skin sensitizer.

**Repeated Dose Toxicity**

Repeated exposure does not cause significant toxic effects.

**Mutagenicity**

Not considered to be a mutagenic hazard.

This product does not contain any carcinogens as listed by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the American Conference of Governmental Industrial Hygienists (ACGIH).

## Section 11. Ecological Information

**Basis for assessment**

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar products.

**Mobility**

Floats on water. Remains on surface of soil.

**Persistence/Degradability**

Expected to be not inherently biodegradable. Persists under anaerobic conditions.

**Bioaccumulation**

Not expected to bioaccumulate.

**Acute Toxicity (Fish, Invertebrates, Algae, Bacteria) and Sewage treatment**

Expected to be practically non toxic, LC/EC/IC 50 > 1000 mg/l

**Other Information**

DIOSHY<sup>®</sup>TPE products (the neat resin or the base product) are high molecular weight polymers which by all accounts are non-toxic and biologically inactive.

## Section 12. Disposal Considerations

**Waste Disposal**

Recover or Recycle if possible, otherwise Incineration, otherwise Licensed Landfill.

**Product Disposal**

Same as for waste disposal.

**Container Disposal**

Remove all packaging for recover or waste disposal.

**Local Legislation**

The recommendations given are considered appropriate for safe disposal. However, local, state, federal, international, or country specific regulations take precedents. They may vary, and they may be more stringent but they must be strictly enforced and complied with.

If this material becomes a waste and has not been chemically altered, it is not considered a hazardous waste as defined by RCRA (40CFR 261).

## Section 13. Transport Information

### US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

### International Air Transportation Association Classification

This material is not classified as hazardous under IATA regulations.

### International Maritime Organization - IMDG

This material is not classified as hazardous under IMDG regulations.

### UN, IMO, ADR/RID, ICAO Code

This material is not dangerous for conveyance under these codes.

## Section 14. Regulatory Information

The regulatory information provided is not intended to be comprehensive. Other local, state, federal, international or country specific regulations may apply to this material.

### EUROPE - EC Classification

Not classified as dangerous under EC criteria.

### US legislation:

US Federal - Superfund Amendment & Reauthorization Act (SARA) Title III:

This material is not regulated under SARA Title III.

US Federal - Toxic Substances Control Act (TSCA) Inventory Status:

Component(s) of this material is (are) listed on the EPA TSCA Inventory of Chemical Substances.

US State - California Safe Drinking Water

This material is not regulated by the California Safe Drinking Water Act.

US State - Toxic Enforcement Act (Proposition 65):

This material is not regulated by the Toxic Enforcement Act (Proposition 65).

US State - New Jersey Right-To-Know List:

This material is not regulated by the New Jersey Right-To-Know Act.

US State - Pennsylvania Right-To-Know List:

This material is not regulated by Pennsylvania Right-To-Know Act.

### International legislation

Canada - Workplace Hazardous Materials Information System (WHMIS):

"This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required." This is NOT a WHMIS controlled product.

## Section 15. Other Information

### Revision #01

Revision Date: 2006/05/01

Revisions since last change:

This document should be made available to all who may handle the product.

### Medical, Healthcare and Cosmetic Applications and Trademark Usage

DIOSHY®TPE products should not be used in any devices or materials intended for implantation in the human body as defined by the U.S. Food and Drug Administration under 21 CFR 812.3(d) and 21 CFR 860.3(d). DIOSHY®TPE products may, in certain circumstances, be used in the following products or applications with prior written approval for each specific product or application: a. Cosmetics (exclusive of packaging or delivery applications). b. Drugs and other Pharmaceuticals (exclusive of packaging or delivery applications). DIOSHY®TPE trade names, trademarks, logos or other similar identifying characteristics should not be used in the manufacture, sale, or promotion of cosmetics, drugs, and pharmaceutical products or other medical/healthcare applications or materials. DIOSHY CO., LTD. has no specific expertise in these markets and applications, and does not intend to perform testing, clinical studies or other investigations of the suitability of its products for specific applications. Each customer or user of DIOSHY®TPE products is solely responsible for determining the suitability of the materials it selects for the intended purpose and acknowledges that it has not relied on any representations of DIOSHY CO., LTD. regarding suitability for use in its intended cosmetics, drugs, pharmaceutical products or materials. Please contact your DIOSHY®TPE Sales Representative for more details before using our products in these specific applications.

**Information on the food packaging clearances of individual products is available from KRATON Polymers.**

### Other information

DIOSHY®TPE and the DIOSHY®TPE logo are trademarks owned by the DIOSHY CO., LTD. of Companies.

### Disclaimer

The information in this document is based on our current knowledge and is intended to describe the product for the purposes of Health, Safety and Environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Advice in this document relates only to the product as originally supplied. Where other ingredients are added in the processing of this product, advice should be sought on their safe handling and use.