

CANOE SPECS	Length	Weight in Fiberglass	Weight in Kevlar®	Weight in Kev/Duraflex	Weight in Ultralight	Weight in Custom Kev	Height at Bow	Height at Stern	Height at Centre	Beam Width	Width at 4" Waterline
16' Ranger	15'10"	70	54	-	48	-	19	19	13	35	33
17' Ranger	17'	74	58	-	52	-	20	20	14	36	33
Yukon	16'8"	70	-	-	-	-	20	20	14	36	34
Escape	14'6"	54	-	-	44	36	19	18	14	35	34
Scout	15'10"	58	-	-	48	40	19	19	13	35	34
Cascade	16'8"	66	56	-	52	-	20	20	14	36	34
Tripper S	16'6"	66	56	-	48	42	19	17	14	32	31.5
Tripper	17'6"	70	60	-	54	44	21	18	15	35	33
14' Prospector	14'	52	42	44	40	-	21	21	15	29	29
16' Prospector	15'9"	70	56	60	52	-	21	21	15	35	33
17' Prospector	17'2"	74	62	68	56	-	21	21	15	36	34
Sea Clipper	18'6"	68	60	-	56	-	23	21	15	36	32
17' Jensen	17'	58	-	-	47	40	17	16	12	33	32
18' Jensen Stock	18'	68	57	-	52	44	19	18	13	33	32.5
Whitewater II	18'6"	72	62	-	56	-	23	18	15	33	32
18'6" MacKenzie	18'6"	78	70	-	62	-	22	22	16	37	35
20' MacKenzie	20'	98	84	-	76	-	24	24	17	40	36
Mac Sport 15	15'	72	62	-	56	-	22	16	15	37	35
Mac Sport 16.5	16'6"	84	68	-	62	-	23	16	16	37	35
Mac Sport 18	18'	98	82	-	76	-	24	16	17	40	36
Packer	14'	42	-	-	34	-	16	16	13	24	27.5
Solitude	15'6"	52	-	-	40	-	16	14	13	28	30
Freedom	16'7"	54	-	-	34	30	16	12.5	12.5	28	28.5
Sea-1	17'9"	65	55	-	-	-	12.5	10.5	14.5	28	24