

Assembly Manual

8x9

PATENTS ARE PENDING



Building Dimensions								
Approximate Size	Storag	e Area	Exterior Dimensions Roof Edge to Roof Edge			Interior Dimensions Wall to Wall		
	Sq. Ft.	Cu. Ft.	Width	Depth	Height	Width	Depth	Height
8′ x 9′	63.75	361.25	93.75″	110"	72"	90″	102"	71″
2.4 m x 2.7 m	5.92 m ²	10.23 m ³	238.13 cm	279.48 cm	182.88 cm	228.6 cm	259.08 cm	180.34 cm

712640303


Before You Begin Site Preparation

Sharp

Edges

2. Level platform.

- 1. Before beginning construction, check local building codes regarding footings, location and other requirements. Study and understand this owner's manual. CAUTION
- 2. Follow all directions and dimensions carefully.
- 3. Follow the step sequence carefully for correct results.
- 4. Be sure all the parts fit together properly before proceeding.
- 5. SAFETY FIRST: Care must be taken when handling various pieces of your kit since some contain sharp edges. Wear work gloves, eye protection and long sleeves when assembling or performing any maintenance on your building.
- 6. GROUND MUST BE LEVEL: Be sure Floor Frames lie flat on ground. To prepare earth bed, remove sod and other debris. Level the high spots with flat shovel and tamp the bed down.
- 7. Separate contents of the carton by the part number while reviewing parts list. Check to be sure that you have all the necessary parts for your building. Refer to Page 32 for the Parts List.




Foundation Recommendations Local building codes vary by region, refer to your local codes for specifications.

Concrete Slab


- 1. Select level site for building.
- 2. Remove 6" of soil for slab.
- 3. Compact 4" gravel in hole.
- 4. Place 6 ml plastic over gravel.
- 5. Construct 2 x 4 form.
- 6. Pour concrete and level.

Slab Dimensions (265,43 cm) 04 1/2" **Door Opening** 92 1/2" (235 cm)



1. Construct with 2 x 4 treated lumber and 5/8" minimum exterior grade plywood using galvanized nails.

Wood Platform



Care & Maintenance

Finish: For long lasting finish, periodically clean and wax the exterior surface. Touch up scratches as soon as you notice them on your building. Immediately clean the area with a wire brush; wash it and apply touch up paint per manufacturer's recommendation.

Roof: Keep roof clean of leaves and snow with long handled, soft bristled broom. Heavy amounts of snow on roof can damage the building making it unsafe to enter.

Doors: Keep doors closed to prevent wind damage.

Fasteners: Regularly check you building for loose screws, bolts, nuts, etc. and retighten them as necessary.

Moisture: With changing temperatures, condensation will accumulate inside the building.

Other Tips: A noncorrosive caulking is helpful to seal the building.





Do Not store swimming pool chemicals in your building. Combustibles and corrosives must be stored in air tight containers.







ASSEMBLY COMMON FOR ALL PANELS











CAUTION

Sharp Edges














Part No	Name	Quantity
	Upper Channel Assembly(painted)	2


















	Part No	Name	Quantity
Pre-Assembly Rear Wallcont		Upper Channel Assembly (painted)	1
Pie-Assembly Real Wall Coll VIV	1	Floor Channel Assembly (unpainted)	1
	10280	Corner Clip	2



























































Step 10 Anchor Building




It is important that building be anchored after construction.


These are recommended ways of anchoring.

Anchor Kit Model No AK100, SAK100 or 68383


Recommended for use with concrete foundation. Contains corner gussets, perimeter clips, hardware, 1/4" masonry drill bit and installation instructions.




Anchor into Wood or Concrete For wood platform. Use Decking Screws. For concrete slab. Use Lag Screws.




Anchor Kit Model No AK4, SAK4 or 60298



Recommended for use with any suggested base. Contains 4 Anchors with Cable, clamps and installation instructions.





Turn Anchors into ground close to building and attach Cable.

Parts List 8x9

Dia. No.	Part Name	Qty	Part No.
1	Wall Panel	23	10307
2	Corner Panel	4	10268
3	Upper Channel - Painted	4	10345
4	Floor Channel - Unpainted	4	10343
5	Channel Splice	12	10323
6	Corner Clip	8	10280
7	Upper Channel - Painted	4	10341
8	Floor Channel - Unpainted	4	10340
9	Wall Panel - Right	1	10316
10	Wall Panel - Left	1	10317
11	Door Jamb	2	10371
12	Header Trim	1	10291
13	Left Gable	2	10293
14	Right Gable	2	10294
15	Header Angle	1	10260
16	Gable Brace	2	10278
17	Gable Brace	4	10279
18	Ridge Beam	4	10348
19	Right Roof Channel	4	10346

Dia. No.	Part Name	Qty	Part No.
20	Left Roof Channel	4	10347
21	Roof Panel	14	10285
22	Roof Panel (left)	2	10287
23	Roof Panel (right)	2	10286
24	Roof Fascia	4	10321
25	Ridge Cap	1	10270
26	Ridge Cap	1	10349
27	Peak Cap	2	
28	Corner Cap	4	
29	Door Panel	2	10310
30	Door Panel	2	10311
31	Vertical Door Brace	1	10363
32	Vertical Door Brace	1	10362
33	Horizontal Door Brace	4	10301
34	Diagonal Door Brace	4	10295
35	Astragal	1	10364
36	Beam	4	10304
37	Ramp	1	10292
38	Vertical Door Brace	2	10361

If you find any parts missing during construction call:

1-800-851-1085

or write:

CUSTOMER SERVICE

1101 North Fourth Street Breese, Illinois 62230

www.sheds.com

Please include your Model Number, Part Number, and Part Name

Keep this Assembly Manual for further reference.

