

2-PIN PLUG TO BARE END

DESCRIPTION

Our DYNAMIX NZ/AU 2m 2-pin plug power lead to bare end (2 core 0.75mm²) is SAA approved and perfect for replacing damaged plugs on electronic equipment or re-wiring existing electronic devices.

FEATURES

- Insulation stripped for easy connection and installation
- SAA Approved
- Fine-stranded copper wire inside
- Flexible plug end
- PU outer Jacket
- Rated Current: 10A
- 2 core 0.75mm²



PRODUCT CODE	DESCRIPTION	LENGTH	COLOUR
C-PB2C75-2	2-Pin Plug to Bare End, 2 Core	2m	Black
C-PB2C75-2WH	2-Pin Plug to Bare End, 2 Core	2m	White

ALSO AVAILABLE:

<p>C-PB3C10-2 2M 3-Pin Plug to Bare End, 3 Core 1mm Cable, Black Colour, SAA Approved</p>	<p>C-PB3C10-2 2M 3-Pin Plug to Bare End, 3 Core 1.5mm Cable, Black Colour, SAA Approved.</p>	<p>C-PB3C10-2 2M 3-Pin Right-Angled Plug to Bare End, 3 Core 1mm Cable, Black Colour, SAA Approved.</p>	<p>C-PB3C10-2 2M 3-Pin Tapon Plug to Bare End, 3 Core 1mm Cable, Black Colour, SAA Approved.</p>
--	---	--	---

Please note we took the up-most care to compile the information in this datasheet. To the best of our knowledge all info provided were correct at the time of creation. Should any specs change we try to update info accordingly. Information are subject to change without notice. In the case that you find any irregularity please inform our team at contactus@dynamix.co.nz

Last updated: 20 April 2020