

Portable DC-AC Inverter

MODEL CODE

IPS-250

FEATURES

- Efficient inverter
- 12V DC input voltage
- Over voltage protection
- Overload protection
- Low voltage protection
- Short circuit protection
- Mobile installation
- Power: 250VA/200 watts



DYNAMIX™

Standard Power Extension Cord

MODEL CODE

LENGTH

PEXT3M	3M
PEXT5M	5M
PEXT10M	10M

Extends a standard wall power point socket, 1mm copper core 10A, SAA approved



Jackson™

Heavy Duty Extension Lead

MODEL CODE

LENGTH

PEXT-HD15	15M
PEXT-HD20	20M
PEXT-HD30	30M

LED featured in centre of socket indicates if cord is live. Clear molded plastic plug and socket. 1.0mm copper core, SAA approved



DYNAMIX™

Extra Heavy Duty Extension Lead

MODEL CODE

LENGTH

PEXT-EHD20	20M
PEXT-EHD30	30M

Industrial and construction site applications LED featured in centre of socket indicates if cord is live. Clear molded plastic plug and socket. 1.5mm copper core, SAA approved



DYNAMIX™

SAA Approved Power Cord

MODEL CODE

LENGTH

TYPE

C-POWERCPP	0.3M	Molded
C-POWERCO	0.5M	Molded
C-POWERCTQ	0.75M	Molded
C-POWERC1	1M	Molded
C-POWERC	1.8M	Molded
C-POWERC3	3M	Molded
C-POWERC4	4M	Molded
C-POWERC5	5M	Molded
C-POWERC BULK	1.8M	Molded*

IEC Power cord, 3 pin to C13, 10A rated, SAA approved



*Boxes of 100, Clear Poly Bag

3 Pin Plug to IEC Female

MODEL CODE

LENGTH

COLOUR

C-POWERCWH	1.5M	White
------------	------	-------

3 pin plug to IEC female, 3 core 1mm cable, 10A rated, SAA approved



Right Angled Power Cord


MODEL CODE

LENGTH

TYPE

C-POWERCR	2M	Molded
C-POWERCR3	3M	Molded
C-POWERCR5	5M	Molded

Standard Australian / NZ power cord with right angle IEC connector, 3 pin to right angle C13, 10A rated, SAA approved



Tapon Ended Power Cord

MODEL CODE

LENGTH

TYPE

C-POWERCT12	1.2M	Molded
C-POWERCT	2M	Molded
C-POWERCT3	3M	Molded

SAA Approved C13 to 3 pin power cord with tapon ended plug. 10A rated



CUSTOM & INTERNATIONAL POWER CORD AND CORD SET LENGTHS AVAILABLE ON REQUEST