



SEA-BSR

Date Prepared: 05/01/2018

Safety Data Sheet

Section 1. Identification

Manufacturer:

Sea-Shield 1 800 673-8886 Sales@sea-shield.com

Product Identification: Sea-Shield Cut & Polish #2

Suggested Use: Use to remove oxidation, minor to moderate scratches, swirls and other imperfections in gel coat surface, and to create a smooth polished finish on gel coat surface.

Section 2. Hazard(s) Identification

Hazard Class & Category Codes	Hazard Statement Codes	Pictograms & Signal Word
Asp. Tox. 1 STOT RE 1	H304: May be fatal if swallowed and enters airways. H372: Causes damage to organs through prolonged and repeated exposure.	Danger

Precautionary	Precautionary Statements
Statements Codes	
P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use
P202	Do not handle until all safety precautions have been read and understood
P262	Do not get in eyes, on skin or on clothing
P301+311+315	IF SWALLOWED: Get immediate medical attention and call a POISON CENTER or doctor/physician
P303+313	IF exposed or concerned: Get medical advice/attention
P404	Store in a closed container
P501	Dispose of contents/container to approved waste facility

Section 3. Composition/Information on Ingredients

Component Name	CAS Number	EC Number	Percentage
Water	7732-18-5	231-791-2	Balance





Petroleum Hydrocarbon	8052-41-3	232-489-3	10-15%
Aluminum Oxide	1344-28-1	215-691-6	10-20%
Light Mineral Oil	8042-47-5	232-455-8	3-6%
Petroleum Hydrocarbon	68476-34-6	270-676-1	1-5%
Acrylic Polymer	N/A	N/A	.005-2%

Section 4. First Aid Measures

Eyes: Flood with large amounts water at least 20 min.; get immediate medical attention if irritation persists. Can cause irritation, redness, tearing, and blurred vision.

Skin: Flush exposed area with water. Remove all contaminated clothing. Prolonged or repeated contact can cause moderate irritation.

Inhalation: If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, calm, and get medical attention. **Oral:** If swallowed, induce vomiting. Vomiting can be induced with syrup of Ipecac. Give fluids until the

vomitus is clear. Get medical attention.

Section 5. Fire Fighting Measures

Flash Point: 200°F

Autoignition Temperature: Not determined **Flammability Limits in Air:** Not determined

Extinguishing Media: Carbon dioxide (CO2) water spray. Dry chemical foam can be used to cool fire-

exposed containers.

Fire Fighting Procedure: Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Evacuate area in case of overheating or fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Static electricity will accumulate and may ignite vapors.

Hazardous Decomposition Products: Carbon oxides and various hydrocarbons.

Section 6. Accidental Release Measures

Containment/Clean Up: Sections 13 and 15 of this MSDS provide information regarding certain Federal and local requirements. Collect for disposal. Clean up remaining materials from spill with suitable absorbent. For large spills provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean area as appropriate as some silicone material, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Observe all personal protection equipment recommendations described in Sections 5 and 8 of this MSDS. Observe all Federal and government regulations that may apply to the cleanup of this material.

Section 7: Handling and Storage

Handling (Personnel): Avoid contact with oxidizing agents. Spilled substance increases risk of slippage.





Storage: Keep container tightly closed.

Section 8: Exposure Controls and Personal Protection

Engineering Controls:

Local Exhaust: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

General exhaust: Recommended

Personal Protective Equipment for Routine Handling:

Eyes: Use proper protection – safety glasses as a minimum. **Skin:** Washing at meal time and end of shift is adequate.

Suitable Gloves: butyl rubber protection gloves

Inhalation: If spraying or other operations that generate an aerosol mist are conducted,

respiratory protection for exposed personnel is recommended.

Precautionary Measures: Avoid eye contact.

Section 9: Physical and Chemical Properties:

Physical Form:LiquidViscosity:Not determinedColor:ClearMelting Point:Not determinedOdor:SlightBoiling Point:Not determined

Specific Gravity @ 25° C: 1.03 Flash Point: 200° F

Solubility in Water: Soluble Vapor Pressure @ 25° C Not determined

VOC content (% by 10-15% pH: 7-8

weight)

Section 10: Stability and Reactivity

Chemical Stability: Stable

Hazardous Polymerization: Will not polymerize

Conditions to Avoid: None known

Materials to Avoid: Strong oxidizing agents and strong acids.

Section 11: Toxicological Information

Acute Toxicity: Irritation to eyes and skin

Chronic: Unknown

Eyes: No data available
Skin: No data available

Sensitization: Not a known sensitizer

Mutagenicity: No evidence for mutagenicity

Carcinogenicity: Contains no ingredients classified as carcinogens by IARC, NTP or OSHA

Reproductive Toxicity: No known reproductive toxicity





Target Organs: None known
Aspiration Hazard: No data available

Section 12: Ecological Information

Fish: No data available
Daphnia: No data available
Algae: No data available

Section 13: Disposal Considerations

Landfill and/or incinerate where permitted in compliance with all applicable Federal, State and local government regulations.

Section 14: Transportation Information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

Section 15: Regulatory Information

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

TSCA Status: All chemical substances in this material are included on or exempted from

listing on the TSCA inventory of chemical substances.

EPA SARA Title III Section 302 Extremely Hazardous None

Chemical Listings Substances

Section 304 CERCLA Hazardous None

Substances

Section 312 Hazard Class Acute No

Chronic No Fire No Pressure No Reactive No

Section 313 Toxic Chemicals Aluminum oxide (1344-28-1) 10-20%

Supplemental State

Compliance Information None





Section 16: Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. Any material supplied is the sole responsibility of the user. All materials may present unknown health hazards and we cannot guarantee that the hazards listed herein are the only hazards that exist.