

Safety Data Sheet

SEA-CCC

Date Prepared: 05/01/2018

Section 1. Identification

Manufacturer:

Sea-Shield
1 800 673-8886
Sales@sea-shield.com

Product Identification: Sea-Shield Ceramic Crew

Suggested Use: The application area should be well-ventilated with good lighting. Avoid direct sun or hot surfaces when applying to glass. If necessary, prep and polish the surface before applying the Crew Ceramic Coating.

Section 2. Hazard(s) Identification

Route of Entry: Inhalation, Ingestion, Skin Absorption, Eye Contact

Target Organs: Respiratory System, Integumentary System, Digestive System and Nervous System.

Inhalation: May cause moderate irritation of the upper respiratory tract. May produce symptoms of CNS depression (headaches, dizziness, nausea, loss of balance, drowsiness) and CNS stimulation (shaking, tremors). Severe overexposure may cause severe CNS depression symptoms such as fatigue or loss of concentration.

Skin Contact: May cause moderate skin irritation.

Eye Contact: May cause irritation and pain.

Ingestion: Harmful by ingestion. May be irritating to the gastrointestinal tract, cause gastric distress and stomach pains.

Hazard Class & Category Codes

NPFA
HMIS III

Hazard Statement Codes

Health = 2, Fire = 3, Reactivity = 1
H*2/F3/PH1

Pictograms & Signal Word



Precautionary Statements Codes

Precautionary Statements

GHS Classifications: Physical, Flammable Liquids, 3
Health, Acute toxicity, 4
Oral Health, Specific target organ toxicity - Single exposure, 3
Environmental, Hazards to the aquatic environment - Acute, 3
Health, Acute toxicity, 4 Dermal
GHS Phrases:
H226 - Flammable liquid and vapour

- H302 - Harmful if swallowed
- H335 - May cause respiratory irritation
- H402 - Harmful to aquatic life
- H312 - Harmful in contact with skin

GHS Precautionary Statements:

- P102 - Keep out of reach of children.
- P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P211 - Do not spray on an open flame or other ignition source.
- P232 - Protect from moisture.
- P240 - Ground/bond container and receiving equipment.
- P242 - Use only non-sparking tools.
- P243 - Take precautionary measures against static discharge.
- P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
- P262 - Do not get in eyes, on skin, or on clothing.
- P264 - Wash hands thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P284 - Wear respiratory protection.
- P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P302+352 - IF ON SKIN: Wash with soap and water.
- P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.
Continue rinsing.
- P314 - Get Medical advice/attention if you feel unwell.
- P332+313 - If skin irritation occurs: Get medical advice/attention.
- P337 - If eye irritation persists: Seek medical attention.
- P342 - If experiencing respiratory symptoms: Seek medical attention.
- P370+378 - In case of fire: Use dry chemical powder, foam, for extinction.
- P374 - Fight fire with normal precautions from a reasonable distance.
- P402+404 - Store in a dry place. Store in a closed container.
- P403+233 - Store in a well ventilated place. Keep container tightly closed.
- P403+235 - Keep cool.
- P410+403 - Protect from sunlight.
- P501 - Dispose of contents/container to licensed waste facility.

Section 3. Composition/Information on Ingredients

Component Name	Percentage
Ambient temperature-curable refractory resin(s)	15-40%
Matting agents	1-5%
Rheology modifiers	0-10 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as significantly hazardous to health or the environment and hence require reporting in this section.

Section 4. First Aid Measures

Eyes: Flood with large amounts water at least 20 min.; get immediate medical attention if irritation persists. Can cause irritation, redness, tearing, and blurred vision.

Skin: Remove all contaminated clothing and shoes. Wash thoroughly with soap and water for at least 15 minutes. Wash all clothing before re-use. If symptoms develop, seek medical attention.

Inhalation: Remove to fresh air. If breathing is difficult, have trained person administer oxygen. If breathing stops, have trained person administer artificial respiration. Maintain an open airway. Loosen tight clothing. If symptoms develop, seek medical attention.

Oral: Rinse mouth out and then drink plenty of water. Only induce vomiting at the instruction of medical personnel. Vomiting may be dangerous. Keep head low so vomit does not enter the lungs. Never induce vomiting or give anything by mouth to an unconscious or convulsing person. Keep patient at rest. Seek immediate medical attention.

Section 5. Fire Fighting Measures

Extinguishing Media: Carbon dioxide, dry chemical powder, foam or alcohol foam.

Fire Fighting Procedures: Evacuate all unnecessary personnel. Shut down motors, pumps, electrical service, and eliminate sources of ignition if safe to do so. Use water spray to cool containers and avoid pressure build-up (do not allow water to mix with product). If fire occurs, isolate area, contain and eliminate fire, then dispose of debris in accordance with official regulations. Stay upwind of material at all times. Wear self-contained breathing apparatus and full protective clothing. May release dense black smoke containing hazardous products of combustion.

Fire and Explosion Hazard: Contains possibly combustible materials. Over-heated containers may rupture. Fumes may be flammable/explosive in air when in the presence of an ignition source. Vapors may travel a significant distance to a source of ignition and flash back.

Sensitivity of Static Charge: Electrostatic charge may build up during handling. Grounding of equipment is required.

Section 6. Accidental Release Measures

Personal Precautions:

Evacuate all unnecessary personnel and surrounding areas, and eliminate all sources of ignition if safe to do so. Wear proper personal protective equipment, especially a self-contained breathing apparatus. Do

not touch or walk through spilled material. Provide adequate ventilation and avoid breathing vapors. Ground all equipment used.

Environmental Precautions:

Contain liquids and prevent discharge into streams, soil, waterways, drains and sewers. Control or stop the loss of volatile material to the atmosphere. Do not apply water to the spill. Spills should be reported, if required, to the appropriate local, state, or federal agencies, especially if environmental pollution has occurred. In case of major release or road spill notify PERS: 1-800-633-8253 (USA & Canada) or 001-1-801-629-0667.

Remove all sparking devices or ignition sources. Product is flammable. Stop leak if without risk. Move containers from spill area. Approach spill from upwind. Cover with an inorganic absorbent, such as vermiculite, perlite, ground clay, or sand; sweep up, and dispose according to local, state and federal regulations. Contaminated absorbent may pose the same hazard as spilled material does. Use spark proof tools and explosion proof equipment. Dispose of via a licensed waste disposal contractor

Section 7: Handling and Storage

Handling Precautions:

This material is rated as flammable.

Avoid vapor formations and use with adequate ventilation.

Avoid breathing fumes.

Vapors are heavier than air and will tend to collect in low areas. Avoid use in confined spaces.

Avoid bodily contact with material.

Wear appropriate personal protective equipment.

Wash thoroughly after handling, avoid contact with eyes.

No eating, drinking or smoking near areas where substance is handled, processed or stored.

Flammable vapours may form explosive mixtures in the air.

Ground coating equipment and containers at all times.

Use non sparking tools.

Isolate, vent, drain, wash and purge systems or equipment before maintenance or repair.

Clean spills immediately.

Storage Precautions:

Keep away from heat, static electricity discharges and all sources of ignition.

Avoid moisture and extreme temperatures.

Avoid shock and friction.

Store in a cool, dry area away from direct sunlight (do not store in temperatures below 50 oF or above 77 oF). Avoid freezing.

Do not allow cross-contamination, and keep away from incompatible materials.

Keep tightly closed when not being used, but vent carefully before using.

Label all containers appropriately.

Do not reuse containers.

Do not store near food or drinks.

Avoid excessive aging.

Store in accordance with local regulations

Section 8: Exposure Controls and Personal Protection

Engineering Controls:

Adequate room ventilation plus local exhaust at points of emission to maintain levels of airborne contaminants below exposure limits. Assure ACGIH TWA and OSHA PEL limits (varies by product) are maintained. Use of fume hoods or closed booths required when product is used in a manner that may generate mist or aerosol.

Personal Protective Equipment for Routine Handling:

HMIS PP, F | Goggles, Chemical Resistant Gloves, Apron (protective industrial clothing recommended along with apron).

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times. Solvent resistant (neoprene, nitrile or other nonporous) recommended.

Eyes: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Chemical splash goggles should be worn at a minimum.

Skin: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Apron and protective industrial coating recommended.

Emergency shower and eyewash facility should be in close proximity. Employ proper hygienic measures after working with material and before eating, smoking or using the lavatory. Fully wash any contaminated clothing.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the regulations of environmental protection legislation.

Completely isolate and thoroughly clean all equipment, piping or vessels with a solvent before beginning maintenance or repairs.

Section 9: Physical and Chemical Properties:

Appearance: Color varies by product

Physical State: Liquid

Odor: Ammoniacal

Spec Grav./Density: 0.8 - 1.0

Solubility: Reacts with water

Viscosity: Varies by product number

VOC: Exempt

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Extreme temperatures, moisture, vapor formation and sources of ignition.

Materials to Avoid: Strong oxidizing agents, strong acids, water and alkalines.

Hazardous Decomposition: Chlorine-containing gases, fluorine-containing gases may be preserved in products containing p-chlorobenzotrifluoride. Carbon dioxide and silicon oxides may be produced from all coating formulations.

Hazardous Polymerization: Will not occur.

Section 11: Toxicological Information

NTP Carcinogen: No

IARC Monographs: No

OSHA Regulated: No

Not known to contain any ingredients recognized as carcinogens by the National Toxicology Program (NTP), the International Agency for Cancer Research (IARC) or the Occupational Safety and Health Administration (OSHA). Reported Human Effects: No human studies have been conducted with this material. The use of recommended protective equipment should minimize any adverse effects.

Reported Animal Effects from various individual chemical components: Oral LD50, rat: >300-2000 mg/kg Vapor LC50, rat 20 g/m³ Skin irritation, rabbit; corrosive. Vapor LC50, rat 4211 ppm Toxicological information may change depending on individual product.

Section 12: Ecological Information

Water hazard Category 2: Contains materials toxic to fish. Avoid disposal in landfills and sewage systems. Avoid release into water sources.

Section 13: Disposal Considerations

This product is not regulated by the EPA. It is the waste generator's responsibility to determine how disposal must occur. Disposal should be made in accordance to federal, state, and local regulations. Minimize or avoid the generation of waste whenever possible. Dispose of waste, unused material and empty containers in a licensed facility. Do not discharge into drains, surface waters or groundwater. Do not mix this product with aqueous or other protic waste streams. Incineration of combustible waste material in a permitted facility in accordance with the local, state and federal regulations is the recommended disposal method.

Section 14: Transportation Information

DOT Class: Flammable Liquid (3) #3 UN #: UN 1263, Class: 3, Proper Shipping Name: Paint or Paint-Related materials

US DOT: Proper Shipping Name: Paint or Paint Related Materials

Hazard Class: 3

UN Number: 1263 Packing Group: III

IATA: Proper Shipping Name: Paint or Paint Related Materials

Hazard Class: 3

UN Number: 1263 Packing Group: III

Section 15: Regulatory Information

U.S. Federal Regulations: TSCA All components are listed or exempted. SARA 302/304/311/312:

Depends on individual product. Individual products may or may not contain chemicals subject to the



reporting requirements of SARA 313. California Proposition 65: Individual products may or may not contain chemicals known to the state of California to cause cancer and birth defects, or other reproductive harm. Canadian DSL Inventory Status: This product contains materials not listed on the Canadian DSL but listed on the NDSL. *tert-Butyl acetate (540885 40.0-60.0%) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR REGULATORY KEY DESCRIPTIONS -----
----- TSCA = Toxic Substances Control Act CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level

Section 16: Other Information

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. Any material supplied is the sole responsibility of the user. All materials may present unknown health hazards and we cannot guarantee that the hazards listed herein are the only hazards that exist.