



SEA-SHIELD®
PREMIUM YACHT PRODUCTS

Sea-Shield
6110 33rd Street East
Brandenton FL 34203
info@sea-shield.com
www.sea-shield.com

Heavy Cut™ #1

Part	Size	Case Size
SEA-HC16	16 OZ	12
SEA-HC1	1 Gallon	4



BENEFITS

- * Removes heavy scratches and oxidation
- * Removes 1500 grit sand paper marks
- * Breaks down evenly for uniform finish

DESCRIPTION

Sea-Shield® Heavy Cut #1 removes heavily oxidized and damaged surfaces on paint and gelcoat.

It can also be used to remove 1500# grit sandpaper scratches. Uniform compounding beads break down while polishing to reduce swirl marks and micro scratches.

Follow with Sea-Shield® Cut & Polish #2 and Sea-Shield® Swirl Remover #3 to restore surface to like-new condition.

DIRECTIONS

Best results are achieved when using a circular polisher (1000-1500 RPM) equipped with a Sea-Shield® Heavy Cutting Pad or Sea-Shield® Cut & Polish Pad. Apply product to pad or surface to be buffed. Spread product before starting machine to reduce product sling-off. Start machine using medium pressure while working in a 2 foot by 2 foot area. Move machine slowly back and forth, keeping pad flat on the surface at all times. Reduce pressure as product begins to dry. Clean buffing pad and rebuffer surface until most of the residue is gone. Wipe remaining residue off using a clean microfiber towel. (Use Sea-Shield® Buffing Lube as needed.)

RECOMEND SURFACE

- Paint
- Gel-coat



Clean

Polish

Protect