



SEA-SHIELD®

PREMIUM YACHT PRODUCTS

Sea-Shield
6110 33rd Street East
Brandenton FL 34203
info@sea-shield.com
www.sea-shield.com

Swirl Remover #3



Part	Size	Case Size
SEA-SR16	16 OZ	12
SEA-SR1	1 Gallon	4

BENEFITS

- * Removes light oxidation
- * Completely erases swirl marks
- * Brings back the ultimate luster

DESCRIPTION

Sea-Shield® Swirl #3 is an exceptional polish designed to remove light oxidation, fine scratches, light chalk, and light swirl marks from both paint and gelcoat surfaces.

DIRECTIONS

Best results are achieved when using a circular polisher (1000-1500 RPM) equipped with a Sea-Shield Yellow Polishing Pad. Apply product to pad or surface to be buffed. Spread product before starting machine to reduce product fling-off.

Start machine using medium pressure while working in a 2 foot by foot area. Move machine slowly back and forth, keeping pad flat on the surface.

Reduce pressure, as product begins to dry.

Clean buffing pad and rebuf surface until most of the residue is gone. Wipe remaining residue off using a clean microfiber towel.

(Use Sea-Shield® Buffing Lube as needed.)

RECOMEND SURFACE

- Paint
- Gelcoat



Clean

Polish

Protect