


# NYC-3H New York City Emergency Light



These rugged steel units have been designed for easy installation and maintenance. All parts and wiring are front accessible. The attractive cabinets fit any décor and are ideal for both commercial and industrial use.

Model No	Watts per head (HIT)	Capacity 90 minutes	Capacity 2 hours	Capacity 3hours	Capacity 4 hours	Weight
12 Volts						
NY3 - 12-60	12	60	47	30	22	14
NY3 - 12-75	12	75	58	38	27	16
NY3 - 12-100	12	100	78	50	36	18
NY3 - 12-125	12	125	94	62	45	20

#### STANDARD FEATURES

- Dual 120/277 volt 60 Hz input, other voltages are optional.
- Fully automatic solid state charger returns battery to full charge after return of AC supply.
- Solid state relay supervision features low battery voltage disconnect, AC lockout and brownout protection.
- High charge and AC ready LED indicators.
- Long life valve regulated lead acid maintenance free battery provide a minimum of 90 minutes of emergency illumination.
- Heavy duty steel construction finished in white powder coat paint.
  Other colors optional.
- Unit comes with two heads.
- Remote test is optional and requires an IRT hand held tester.
- MADE IN THE USA

## **Sales Department**

(T) 800-480-0707

sales@emergencylights.net www.emergencylights.net

#### **AGENCY APPROVALS**

ETL Listed to UL924.

Meets or exceeds the requirements of the National Electrical Code and NFPA 101 Life Safety Code.

NYC approval calendar number 41262



### OPTIONS Add suffix

- -B Black
- -G Gray
- -E Self-diagnostics
- -V Voltmeter<sup>1</sup>
- -A Ammeter<sup>1</sup>
- -RT Remote test
- -TD Time delay relay
- -0H No heads
- -1H 1 head
- -3H 3 heads
- -ML Metal heads
- -SM Side mounted hea
- -CP 3 foot cord and plu
- -NI Nickel cadmium battery

Note: 1 Only one meter may be installed.

Optional lamps are available. See lamp availability chart page T-1 for proper suffix.

#### WARRANTY

See warranty information at back of catalog for details.