

ELX400 SQ Series (Escort II)

Thermoplastic LED Exit & Combination Units



Fully adjustable SQ heads can be configured for top mounting, side mounting, or anywhere in between without disassembly or re-wiring. The ELXN400 SQ Programmable Series confronts job site mounting situations "head-on."

Standard Features

- Comes with two fully adjustable glare-free SQ light heads for egress light, with two (2) 6V 5.4 watts DC T5 wedge base lamps for emergency mode.
- Low power consumption – LED lamps are operated in normal (AC input) and emergency (DC input) modes.
- Injection-molded UV stabilized thermoplastic housing, faceplates, and canopy. UL 94, 5Va flame rating. Two faces, back plate, and canopy.
- Available with a sealed, maintenance-free Lead-Calcium battery. Additional battery available for 12 watts remote load or extended unit run time (see How To Order).
- 120/277VAC dual voltage operation. LED indicator light and push button test switch. Remote capacity exit with two heads may power additional remote heads up to 6 Volt, 12 watts. Remote capacity exit with no heads may power additional remote heads up to 6 Volt, 22 Watts. Low voltage battery disconnect
- Innovative, snap-together design allows for fast installation. Wall or ceiling mounting. Canopy snaps to housing with a twist-lock feature tightly securing the canopy to the housing. Replaceable directional chevron inserts are easily removed and reinserted.
- UL Listed. Complies with NEC, Life Safety Code and OSHA. Damp location listing is standard on all models.
- 3-year full warranty, excluding lamps, pilot lights and fuses.

Accessories (order as a separate item)

Wire Guard (heads in any position)	WG10-E
Replacement battery860.0004-E
Replacement lamp570.0012-E

* Do not exceed rated unit capacity.

SALES DEPARTMENT

(T) 800-480-0707
sales@emergencylights.net
www.emergencylights.net

How to Order (example)

ELXN400	R	2SQ	R	-AD										
<p>Series Self-powered</p> <p>Examples:</p> <table border="1"> <tr> <th>RED Stencil Face Models</th> <th>GREEN Stencil Face Models</th> </tr> <tr> <td>EXLN400R-2SQ</td> <td>EXLN400G-2SQR</td> </tr> <tr> <td>ELXN400R-0R-AD</td> <td>ELXN400G-2SQ</td> </tr> <tr> <td>ELXN400R-2SQR</td> <td></td> </tr> <tr> <td>ELXN400R-2SQR-AD</td> <td></td> </tr> </table>	RED Stencil Face Models	GREEN Stencil Face Models	EXLN400R-2SQ	EXLN400G-2SQR	ELXN400R-0R-AD	ELXN400G-2SQ	ELXN400R-2SQR		ELXN400R-2SQR-AD		<p>Stencil Face (letters) R= Red G= Green</p>	<p>Light Heads -0= Combo no heads* -2SQ= Lamp standard 6V 5.4W</p> <p>*Only available with Remote Capacity AD and red stencil</p>	<p>Capacity Indicator Blank= No remote capacity R= remote capacity*</p> <p>* Do not exceed rated unit capacity.</p>	<p>Options Blank= No options -AD= Advance Diagnostics*</p> <p>*Only available with Remote Capacity and red stencil</p>
RED Stencil Face Models	GREEN Stencil Face Models													
EXLN400R-2SQ	EXLN400G-2SQR													
ELXN400R-0R-AD	ELXN400G-2SQ													
ELXN400R-2SQR														
ELXN400R-2SQR-AD														

Outline and Dimensions

Dimensions are approximate and subject to change.

