

There is Power Mobility. And then there's
**POWERFUL
MOBILITY**



MiniRider Folding

Call **1-800-944-1997** or visit us at www.evrider.com

There is Power Mobility. And then there's **POWERFUL MOBILITY**



Expand Dimension (L x W x H mm) (L x W x H inch)	1300mmx510mmx960mm 59.1" x23.1" x43.6"
Fold Dimension (L x W x H mm) (L x W x H inch)	550mmx510mmx615mm 25" x23.2" x28"
Weight w/i battery without battery	34.3 kg / 75.5 lbs 27 kg / 59.4 lbs
Battery	10 AH x 2
Controller	DYNAMIC DR50
Front Wheel Size	150x30 Solid
Rear Wheel Size	200x50 Solid
Brake System	Electromagnetic brakes
Control Method	By speed control lever
Max Speed Forward	6.4km/h / 4mph

Cruising range	9 miles /14.4 km (10AH)
Max Loading	115 kg / 253 lbs
Drive System	Direct drive the rear wheels
Motor Specifications	270w x 24V x 1pcs
Frame Construction type and Materials	Aluminum
Battery Charger type and Input Voltage	off-board Input AC 100-240V, Output DC 24V, 1.5 Amp
Suspension	N/A
Safety Features	Anti-tip wheel
Where the device is to be used	Pavement,Single Carriage road and Pedestrian area

(*) SPECIFICATION PERFORMANCE IS DETERMINED IN THE LABORATORY SETTING BASED ON IDEAL CONDITIONS (MINIMAL FRICTION, NO WIND AND CONTROLLED TEMPERATURE AND PRESSURE WITH AN AVERAGE STANDARD WEIGHT). ACTUAL PERFORMANCE WILL BE DIFFERENT THAN RESULTS OBTAINED DURING LABORATORY TESTING.

Call **1-800-944-1997** or visit us at **www.evrider.com**