

Plug-In Appliance Module, ZL-PA-100

Overview

ZL-PA-100 is designed to provide easy Z-Wave control for plug-in appliances and lighting that require On/Off operation. Simply plug the ZL-PA-100 into any standard outlet and the appliance or lamp you wish to control, up to 1800W, into the ZA-PA-100. Add to your Z-Wave network and enjoy custom scenes and scheduled timed events when you're either home or away.

Features

- Wirelessly schedule and control any lamp or small appliance
- Supports S2 and SmartStart for easy, secure inclusion
- Space-saving design does not block second outlet or obstruct furniture placement
- One switched outlet
- Plug-in anywhere indoors
- Large back lit button for local control
- Works with all Certified Z-Wave Controllers
- Internal resettable fuse to protect from surge current

Technical Specifications

Electrical

- Max Load 900W Incandescent, 200W CFL/LED, 1/2 HP Motor, 15A Resistive
- Input: 120VAC, 60Hz, 15A
- Operating Temp. Range: 32-104°F (0-40°C)
- UL and CSA listed
- Requires grounded, three-prong, outlet

Z-Wave

- US Region, 908.4MHz, 916MHz
- Complies with FCC Part 15, Class B
- Z-Wave PLUS, S2 Security, SmartStart
- Z-Wave signal repeater
- Network-Wide-Inclusion
- Over-The-Air (OTA) firmware upgrade capable
- Configurable parameters supported

Physical Size

3.27" X 2.13" X 1.5" With plug: 3.27" X 2.13" X 2.32"





Advanced Configuration

Parameters

#	Description	Values	Default	Bytes
3	Nightlight	When value = 0, the LED indicator will be OFF when the connected appliance is ON, and the LED indicator will be ON when the connected appliance is OFF. If value = 1, the LED indicator will be OFF when the connected appliance is OFF, and the LED indicator will be ON when the connected appliance is ON. If value = 2, the LED indicator will be always OFF regardless of the load status.	0	1