



Screen Drying Cabinet

To get the fastest turn-around during production you must save time wherever possible. The HIX® SD-2632 screen drying cabinet is designed to do just that. Eight innovative angled drying racks are designed to maximize the air flow and dry both coated and reclaimed screens faster with its filtered air delivery system.

The SD-2632 will not only cut drying time by hours but will also nearly eliminate the time-consuming task of fixing pin holes. Optimally spaced air knives are built into the corrosion-resistant galvanized walls to deliver even-heated air across each screen.

You can use the 36.5" x 35" counter-top as a space-saving table for your HIX® Spectrum LED Exposure unit. NOTE: The maximum temperature inside the cabinet is 30°F above room temperature with a maximum temperature of 110°F.



Screen Drying Cabinet

Overview

- Quickly dries screen emulsion as well as wet recycled screens, in a clean dust-free environment.
- Space for 8 screens with a maximum size of 26" x 32".
- Innovative angled-rack system. Screens are placed on 10 degree sloping shelves, allowing for emulsion to remain untouched by the shelves while drying.
- Filters provide clean air to the drying chamber, avoiding dust and pinholes in the emulsion.
- Air knives direct heat to each individual screen slot, guaranteeing that each screen and the emulsion properly dry & cure.
- Galvanized interior resists corrosion from evaporating emulsion and other chemicals.
- Countertop of 36.5" X 35" allows for space to locate the HIX® Spectrum LED Exposure unit, saving space in your shop.



FEATURES

- All Metal Construction
- Space for 8 screens with a maximum size of 26" x 32"
- Fan: 200cfm
- BTU: 1600
- Lifetime warranty on the frame
- 1 year warranty on all electronics

TEMPERATURE RANGE

Off - 110°F (43°C) maximum inside cabinet temperature



DIMENSIONS (W,H,D)

Width: 36 1/2 inches

Height: 34 7/8 inches

Depth: 35 inches

Weight: Dryer only 200 lbs

SHIPPING DIMENSIONS

Shipping Width: 44 inches

Shipping Height: 44 inches

Shipping Depth: 44 inches

Shipping Weight: 250 lbs*

ELECTRICAL

120 Volt / 60 Hz

1600 Watts

13 Amps

220 Volt / 60 Hz

1600 Watts

7.2 Amps

* Single machine will ship freight on a pallet. Request lift-gate or indicate residential shipping is necessary.



HIX® Corporation Graphics Division
Product improvement may require
specifications to change without notice



© 2022 HIX® Corporation

hixcorp.com

800-835-0606

1201 E. 27th Terrace
Pittsburg, KS 66762
USA



All specifications are subject to change without notice.

GSS-SD_2022A