

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020
Revision Date : 04/30/2020

Ref. 130000129166

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ARTISTRI® BRITE P5400 BLACK PIGMENT INK
Product Use : Printing ink

Restrictions on use : Do not use product for anything outside of the above specified uses.
Manufacturer/Supplier : DuPont
974 Centre Road
Wilmington, DE 19805, USA

Product Information : 1-302-996-8439
Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)
Transport Emergency : +1-800-424-9300 (outside the U.S. & Canada +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Product hazard category
Specific target organ toxicity - repeated exposure : Category 2

Label content
Pictogram :



Signal word : Warning

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020 Ref. 130000129166
Revision Date : 04/30/2020

Hazardous warnings : May cause damage to organs through prolonged or repeated exposure.
(Kidney)

Hazardous prevention : Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
measures : Get medical advice/ attention if you feel unwell.
Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 20 - 30 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Ethane-1,2-diol	107-21-1	1 - 10 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice : Never give anything by mouth to an unconscious person. When symptoms persist or in all cases of doubt seek medical advice.

Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If breathing is irregular or stopped, administer artificial respiration. Get medical attention.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020 Ref. 130000129166
Revision Date : 04/30/2020

Eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical advice/attention.

Ingestion : If swallowed, call a poison control centre or doctor immediately. Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center.

Most important symptoms/effects, acute and delayed : No applicable data available.

Protection of first-aiders : No applicable data available.

Notes to physician : No specific intervention is indicated. Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray, Dry chemical, Carbon dioxide (CO₂)

Unsuitable extinguishing media : No applicable data available.

Specific hazards : Hazardous decomposition products formed under fire conditions. (see also section 10) Avoid breathing decomposition products.

Special protective equipment for firefighters : Exposure to decomposition products may be a hazard to health. Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Evacuate personnel to safe areas. Stop spill/release if it can be done with minimal risk. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020 Ref. 130000129166
Revision Date : 04/30/2020

- Safeguards (Personnel) : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Wear suitable protective equipment.
- Environmental precautions : Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Clean contaminated floors and objects thoroughly while observing environmental regulations.
- Spill Cleanup : Contain spill. Soak up with inert absorbent material. Collect and contain contaminated absorbent and dike material for disposal. Keep in suitable, closed containers for disposal. Ventilate the area. Clean contaminated floors and objects thoroughly while observing environmental regulations.
- Accidental Release Measures : Dispose of in accordance with local regulations.

SECTION 7. HANDLING AND STORAGE

- Handling (Personnel) : Avoid inhalation, ingestion and contact with skin and eyes. Do not use in areas without adequate ventilation. For personal protection see section "Exposure controls/personal protection"
Handle in accordance with good industrial hygiene and safety practice. Keep container closed. Keep away from food and drink. Wash hands before eating, drinking, or smoking. Remove contaminated clothing and protective equipment before entering eating areas. Wash contaminated clothing before re-use.
- Handling (Physical Aspects) : Normal measures for preventive fire protection.
- Dust explosion class : No applicable data available.
- Storage : Keep containers tightly closed in a cool, well-ventilated place. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. Do not reuse empty container.
Stable under normal conditions.
- Storage period : No applicable data available.
- Storage temperature : No applicable data available.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering controls : Ensure adequate ventilation. Maintain air concentrations below occupational



ARTISTRI® BRITE P5400 BLACK PIGMENT INK

Version 6.0

Issue Date : 11/19/2020 Ref. 130000129166
 Revision Date : 04/30/2020

exposure standards. General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable limits.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

Hand protection

: Material: Impervious gloves
 Additional protection: Gloves must be inspected prior to use., Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough., The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other., The exact break through time can be obtained from the protective glove producer and this has to be observed., Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection

: Wear safety glasses or coverall chemical splash goggles.

Skin and body protection

: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Lightweight protective clothing and safety shoes are recommended.

Exposure Guidelines

Exposure Limit Values

Ethane-1,2-diol			
TLV	(ACGIH)	25 ppm	TWA Vapour
TLV	(ACGIH)	50 ppm	STEL Vapour
TLV	(ACGIH)	10 mg/m3	STEL Inhalable fraction, Aerosol only
PEL (Permissible Exposure Limit)	(OSHA)	50 ppm 125 mg/m3	C
AEL *	(DuPont)	10 mg/m3	8 & 12 hr. TWA Particulate.
AEL *	(DuPont)	50 ppm	8 & 12 hr. TWA Vapor.

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020
Revision Date : 04/30/2020

Ref. 130000129166

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : liquid
Form : liquid
Color : black

Odor : not significant

Odor threshold : No applicable data available.

pH : 7 - 9

Melting point/range : No applicable data available.

Boiling point/boiling range : Boiling point
100 °C (212 °F)

Flash point : > 93 °C

Evaporation rate : Slower than Ether

Flammability (solid, gas) : No applicable data available.

Upper explosion limit : No applicable data available.

Lower explosion limit : No applicable data available.

Vapour Pressure : No applicable data available.

Vapour density : No applicable data available.

Specific gravity (Relative density) : No applicable data available.

Water solubility : No applicable data available.

Solubility(ies) : No applicable data available.

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020 Ref. 130000129166
Revision Date : 04/30/2020

Partition coefficient: n-octanol/water : No applicable data available.
Auto-ignition temperature : No applicable data available.
Decomposition temperature : No applicable data available.
Viscosity, kinematic : No applicable data available.
Viscosity, dynamic : No applicable data available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : The product is chemically stable under recommended conditions of storage, use and temperature.
Stable at normal temperatures and storage conditions.
Possibility of hazardous reactions : None reasonably foreseeable.
Conditions to avoid : Avoid extreme heat. Do not freeze.
Incompatible materials : Acids, bases and strong oxidizing agents
Hazardous decomposition products : No decomposition if stored and applied as directed.
Under fire conditions:, Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

ARTISTRI® BRITE P5400 BLACK PIGMENT INK
Further information : There is no data available for this product.
Ethane-1,2-diol
Inhalation : no data available
Inhalation :
Dermal LD50 : > 3,500 mg/kg , Mouse


ARTISTRI® BRITE P5400 BLACK PIGMENT INK

Version 6.0

Issue Date : 11/19/2020 Ref. 130000129166
 Revision Date : 04/30/2020

Oral LD50	:	1,650 mg/kg , Cat
Skin irritation	:	No skin irritation, Rabbit
Eye irritation	:	No eye irritation, Rabbit
Skin sensitization	:	Does not cause skin sensitisation., human
Repeated dose toxicity	:	Oral Rat - Target Organs: Kidney Kidney damage
Carcinogenicity	:	Not classifiable as a human carcinogen. Animal testing did not show any carcinogenic effects.
Mutagenicity	:	Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Reproductive toxicity	:	No toxicity to reproduction No effects on or via lactation Animal testing showed no reproductive toxicity.
Teratogenicity	:	Evidence suggests the substance is not a developmental toxin in animals.

Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

Material	IARC	NTP	OSHA
Carbon black	2B		
Carbon black	2B		

SECTION 12. ECOLOGICAL INFORMATION

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020 Ref. 130000129166
Revision Date : 04/30/2020

Aquatic Toxicity

Ethane-1,2-diol

96 h LC50 : Pimephales promelas (fathead minnow) 72,860 mg/l
96 h ErC50 : Pseudokirchneriella subcapitata (green algae) 6,500 mg/l
48 h EC50 : Daphnia magna (Water flea) > 100 mg/l OECD Test Guideline 202

Environmental Fate

Ethane-1,2-diol

Biodegradability : Readily biodegradable. 90 - 100 % OECD Test Guideline 301

Bioaccumulation : Bioaccumulation is unlikely.

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal methods - Product : If recycling is not practicable, dispose of in compliance with local regulations. Never place unused product down any indoor or out door drain.

Waste disposal methods - Container : Do not reuse empty container. Contaminated/not cleaned containers should be treated/handled like product waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and Federal Regulations, as well as industry Standards.

Contaminated packaging : No applicable data available.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.
Regulated by DOT/49CFR as Combustible Liquid when transported in a bulk package (≥ 119 gallons(450 litres)).

**ARTISTRI® BRITE P5400 BLACK PIGMENT INK**

Version 6.0

Issue Date : 11/19/2020
Revision Date : 04/30/2020

Ref. 130000129166

SECTION 15. REGULATORY INFORMATION

- TSCA : In compliance with TSCA-active Inventory requirements for commercial purposes.
- SARA 311/312 Hazard classification : Specific target organ toxicity (single or repeated exposure)
- SARA 313 Regulated Chemical(s) : The following components are subject to reporting levels established by SARA Title III, Section 313: Ethane-1,2-diol, 2,2' -oxybisethanol
- California Prop. 65 : This product can expose you to substances including Distillates (petroleum), hydro- treated light, which is/are known to the State of California to cause cancer, and Ethane-1,2-diol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

The DuPont Oval Logo, DuPont™ and all products denoted with ® or ™ are trademarks or registered trademarks of affiliates of DuPont de Nemours, Inc.

Issue Date : 11/19/2020
Revision Date : 04/30/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.