

DT

Membrane Cable Grommets





EN 45545-2 ECOLAB ROHS Compliant Germany

up to NEMA

c**91**0s IP54

Product Description

The DT cable grommets are designed for standard cables (without connectors). A large number of cables can be routed utilizing minimal space.

DT grommets are designed to fit in KT large grommet spaces:

KEL(-U)	6 - 25
KEL-FG	26 - 27
KVT	32 - 36
KFI 182	46

The DT grommets are also perfectly suitable for the assembly of subsequently terminated cable harnesses.

Advantages

- Combination of routing pre-terminated and standard cables with one cable entry frame
- Enables subassembly of cable harnesses
- High packing density

Specifications

Material Elastomer

Flame class UL94-Vo, self-extinguishing

Protection class IP54

Temperature - 40°C to + 90°C (static)
Properties Halogen free, silicone free

Accessories

ST-B Plugs 74

Description	Туре	Order No.	Number of cables	PU
41.5	DT 1	41500	12× max. 6.5 mm 2× max. 12.2 mm	10
96 0000 0000 0000	DT 2	41510	16× max. 7.1 mm	10
41,5	DT 3	41520	4× max. 6.5 mm 3× max. 9.5 mm 3× max. 11.3 mm	10
90 00 00 00 00 00 00 00 00 00 00 00 00 0	DT 4	41530	9× max. 9.5 mm	10