

LED PANEL LIGHT – CROSS REFERENCE



					
MANUFACTURER	FINDER - 7L	STEGO - LED025	STEGO - LED025 ECOLINE	STEGO - VARIOLINE 021/022	PHOENIX - PLDE400W500
MOUNTING *	M - V	M - V - C	M - V	M - V	C
LIGHT OUTPUT	600lm / 1200lm	400lm	400lm	1080lm / 1730lm	560lm
INSTALLATION	PUSH-IN , CONNECTORS	PUSH-IN , CONNECTORS	PUSH - IN	CONNECTORS	CONNECTORS
SUPPLY VOLTAGE	110...230VAC/DC - 12...48VAC/DC	100...240VAC - 24...48VDC - 12VDC	100...240VAC - 110VDC - 24...48VDC	240VAC	24VDC
AMBIENT TEMPERATURE	- 30 + 50 °C	- 30 + 60 °C	- 30 + 40 °C	- 30 + 60 °C	- 25 + 60 °C
LIGHT COLOR	5000 K	6500 K	6500 K	6500 K	5000 K
PROTECTION CATEGORY	IP 20	IP 20	IP 20	IP 20	IP 20
RATED POWER	9 / 13 W	5 W	5 W	11 / 16 W	5 W
SWITCH	ON/OFF SWITCH, PIR	ON/OFF SWITCH, PIR	ON/OFF SWITCH, PIR	ON/OFF SWITCH, PIR	ON/OFF SWITCH
APPROVALS		   	  	 	
* M: MAGNETS					
V: SCREW					
C: CLIP					

LED PANEL LIGHT – CROSS REFERENCE



					
MANUFACTURER	FINDER - 7L	RITTAL - 2500	FANDIS - FLL	FANDIS - CLG-L	SEIFERT - SL4000
MOUNTING *	M - V	M - V - C	V - M	V	M - C
LIGHT OUTPUT	600 lm / 1200 lm	400 lm / 1200 lm	300 lm	400 lm	300 lm / 700 lm
INSTALLATION	PUSH-IN , CONNECTORS	PUSH-IN , CONNECTORS	PUSH-IN , CONNECTORS	CONNECTORS	CONNECTORS
SUPPLY VOLTAGE	110...230VAC/DC - 12...48VAC/DC	100...240VAC - 24VDC	110,240VAC - 12 - 24 - 48VDC	115...230VAC - 230VAC	120 - 240VAC - 24VDC
AMBIENT TEMPERATURE	- 30 + 50 °C	- 20 + 55 °C	- 30 + 60 °C	- 30 + 50 °C	- 30 + 70 °C
LIGHT COLOR	5000 K	4000 K	7000 K	6500 K	6500 K
PROTECTION CATEGORY	IP 20	IP 20	IP 20	IP 20	IP 20
RATED POWER	9 / 13 W	9 W	5 W	7 W	7 W
SWITCH	ON/OFF SWITCH, PIR	ON/OFF SWITCH, PIR	ON/OFF SWITCH, PIR	ON/OFF SWITCH	ON/OFF SWITCH, PIR
APPROVALS		  			
* M: MAGNETS					
V: SCREW					
C: CLIP					