



Click to shop online @ www.trimantec.com or call 336-767-1379

PFS|SKL

EMC Shield Clamps for Bus Bar



Type	Order No.	Shield diameter	PU
PFS SKL 1.5-3	36786.1	1.5 - 3 mm	10
PFS SKL 3-6	36786.2	3 - 6 mm	10
PFS SKL 6-8	36786.3	6 - 8 mm	10
PFS SKL 8-11	36786.4	8 - 11 mm	10
PFS SKL 12-16	36786.5	12 - 16 mm	10
PFS SKL 17-22	36786.6	17 - 22 mm	10
Bus bar 10 x 3 mm	36100	10 x 3 x 1000 mm*	1

* Other lengths available on request

Product Description

PFS|SKL shield clamps can be used for shielding single cables. The shield clamps are easy to use and enable a reliable shielding of cables.

The PFS|SKL is mounted by snapping on a 10 x 3 mm bus bar.

Advantages

- Optimal contact of the cable shield
- Simple and tool-free assembly
- Permanent and continuous spring load on the cable shield, no adjustment of the spring load required
- Vibration proof, maintenance free
- High packing density due to optimized arrangement possibilities

Specifications

Material

SKL-clamp	Spring steel, zinc plated
PFS-foot	Spring steel
Bus bar	Cu, tin plated
	Current load 140 A

Accessories

KEL-EMC-PF Bracket	119
Stripping tool	113