

ZL

Strain Relief Plates for Screw Assembly



Click to shop online @ www.trimantec.com or call 336-767-1379



Product Description

The strain relief plate ZL is used for static or dynamic applications for organizing and securing cables on machines, control panels or cable carriers.

The undercut on the comb shaped profile provides secure strain relief according to EN 50262 / 62444. Fixation of the cables is achieved by using cable ties.

For multilayer installation please use distance bushings, see Page 85.

Advantages

- Simple assembly
- Cost-effective
- High packing density
- Universal usage

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
Temperature	- 40°C to + 140°C (static)
Properties	Halogen free, silicone free

Accessories

DH Distance bushings	85
KB Cable ties	159

Type	Order No.	Length L1	Length L2	No. of teeth	PU
ZL 39	32222	38.5 mm	19.5 mm	3	10
ZL 60	32224	59.5 mm	43.5 mm	4	10
ZL 70	32226	69.1 mm	43.5 mm	5	10
ZL 87	32228	86.5 mm	68 mm	6	10
ZL 103	32230	102.5 mm	84 mm	7	10
ZL 121	32232	121 mm	102.5 mm	8	10
ZL 140	32234	139.5 mm	121 mm	9	10
ZL 180	32236	180 mm	157 mm	12	10

