



Click to shop online @ www.trimantec.com or call 336-767-1379




KEL-ER also available with V2A screws.



KEL-ER on request also available with threaded bushings.

Type	Order No.	Grommets small large	PU	Description
------	-----------	---------------------------	----	-------------

KEL-ER 16 8	48168	8 -	10	
KEL-ER 16 8 with V2A screws	48168.200	8 -	10	
KEL-ER 16 5	48165	4 1	10	
KEL-ER 16 5 with V2A screws	48165.200	4 1	10	
KEL-ER 16 2	48162	- 2	10	
KEL-ER 16 2 with V2A screws	48162.200	- 2	10	

KEL-ER 16 Cable Entry Frames



IP65

Product Description

Split cable entry system for routing and sealing pre-terminated cables, providing a protection class of IP65 / up to NEMA 4X and strain relief for cable diameters from 2 to 16 mm (KT 2 - 15) and 16 to 34 mm (KT 16 - 34). The new cable entry system is easy to install. Cable grommets are placed into compartments and are securely fixed to the frame during assembly. The KEL-ER 16 frame matches exactly the cut-out dimensions for 16-pole standard industrial connectors.

Advantages

- Warranty on pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and grommets
- Strain relief according to EN 50262 / 62444
- Vibration proof

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
Protection class	IP65, with gasket and correct selection of single grommets (certified according to DIN EN 60529:2000-09)
Temperature	- 40°C to + 140°C (static)
Properties	Halogen free, silicone free
Cut-out dimensions	36/46 x 86 mm / Page 176 - 177
Height KEL	17 mm

Accessories

KT Cable grommets	38 - 40
KEL-EMC Cable collectors	118 - 120