



Click to shop online @ www.trimantec.com or call 336-767-1379



V2A anti-corrosive
KEL-ER also available with V2A screws.





KEL-ER on request also available with threaded bushings.



Split grommets



| Type | Order No. | Grommets small large | PU | Description |
|------|-----------|---------------------------|----|-------------|
|------|-----------|---------------------------|----|-------------|

| | | | | |
|--------------------------------|-----------|-----|----|---|
| KEL-ER 10 6 | 48216 | 6 - | 10 |  |
| KEL-ER 10 6 with V2A screws | 48216.200 | 6 - | 10 | |
| KEL-ER 10 3 | 48212 | 2 1 | 10 |  |
| KEL-ER 10 3 with V2A screws | 48212.200 | 2 1 | 10 | |

Product Description

Split cable entry system for routing and sealing pre-terminated cables, providing a protection class of IP65 / up to NEMA 4X and strain relief for cable diameters from 2 to 16 mm (KT 2 - 15) and 16 to 34 mm (KT 16 - 34). The new cable entry system is easy to install. Cable grommets are placed into compartments and are securely fixed to the frame during assembly. The KEL-ER 10 frame matches exactly the cut-out dimensions for 10-pole standard industrial connectors.

Advantages

- Warranty on pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and grommets
- Strain relief according to EN 50262 / 62444
- Vibration proof

Specifications

| | |
|------------------------|--|
| Material | Polyamide (PA) |
| Flame class | UL94-Vo, self-extinguishing |
| Protection class | IP65, with gasket and correct selection of single grommets (certified according to DIN EN 60529:2000-09) |
| Temperature Properties | - 40°C to + 140°C (static) |
| Properties | Halogen free, silicone free |
| Cut-out dimensions | 36 / 46 × 65 mm / Page 176 - 177 |
| Height KEL | 17 mm |

Accessories

| | |
|--------------------------|-----------|
| KT Cable grommets | 38 - 40 |
| KEL-EMC Cable collectors | 119 - 120 |