

KEL-JUMBO

Cable Entry Frames



Click to shop online @ www.trimantec.com or call 336-767-1379



V2A anti-corrosive
KEL-JUMBO also available with V2A screws.

1

Product Description

The KEL-JUMBO cable entry system for installation of cables and conduits with a diameter of up to 65 mm, especially suited for supply cables.

The innovative grommet design enables dynamic and flexible movement.

We recommend round cut-outs, which can be made using standard tools.

Suggested cut-out: cable diameter +15 - 20%.

Advantages

- Installation of cables up to 65 mm
- KTF grommets allow dynamic and flexible movement
- Retrofitting and maintenance can be carried out easily and quickly
- Strain relief according to EN 50262 / 62444

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
Protection class	IP54
Temperature	- 40°C to + 140°C (static)
Properties	Halogen free, silicone free
Cut-out dimensions	Round, cable diameter +15%

Accessories

KTF Cable grommets	49
KDR-ESR Base plates	136 - 137
KDR2 Split base plates	138 - 139
MP Module plates	146

Description	Type	Order No.	Dimension length width height	PU
	KEL-JUMBO 1	42360	110 x 116 x 35	1
	KEL-JUMBO 1 with V2A screws	42360.200	110 x 116 x 35	1
	KEL-JUMBO 2	42350	200 x 116 x 35	1
	KEL-JUMBO 2 with V2A screws	42350.200	200 x 116 x 35	1