

KEL-QTA

Pluggable Cable Entry Frames



Click to shop online @ www.trimantec.com or call 336-767-1379



1

Product Description

The KEL-QTA easily routes pre-terminated and standard cables without using tools for assembly.

Advantages

- Quick assembly without tools
- High packing density by using multi-grommets
- Simple assembly and disassembly in case of change or service
- Routing of pre-terminated and standard cables in a high packing density
- Suitable for standard cut-outs






Specifications

Material	Elastomer
Flame class	UL94-Vo, self-extinguishing
Protection class	IP54, with correct selection of the cable grommets QT
Temperature	- 40°C to + 90°C (static)
Properties	Halogen free, silicone free

Type A:	For wall thickness 1.5 - 2.5 mm
Type B:	For wall thickness 2.8 - 4 mm

Accessories

QT Cable grommets	56
ST-B Plugs	74
FP Flanged plates	148 - 153

Description	Type	Order No. Type A	Order No. Type B	Cut-out [mm]	Cables	PU
	KEL-QTA 24 2 - DP 18	43642	43643	112 × 36	pre-terminated 2× 3 - 15 mm conventional 16× max. 7 mm 1× max. 12 mm 1× max. 16 mm	10
	KEL-QTA 24 4	43644	43645	112 × 36	pre-terminated 4× 3 - 15 mm	10
	KEL-QTA 10 1 - DP 18	43655	43658	65 × 36	pre-terminated 1× 3 - 15 mm conventional 18× max. 5 mm	10
	KEL-QTA 10 2 - DP 6	43656	43659	65 × 36	pre-terminated 2× 3 - 15 mm conventional 6× max. 5 mm	10
	KEL-QTA-B4	43660	-	45.5 × 45.5	pre-terminated 4× 3 - 15 mm	