

KEL-U-B

Cable Entry Frames



Click to shop online @ www.trimantec.com or call 336-767-1379



Split grommets



V2A
anti-corrosive

KEL-U-B also available with
V2A screws.



KEL-U-B on request also available
with threaded bushings.

1

IP54

Product Description

Split cable entry system for routing pre-terminated cables providing a protection class of IP54. Routing, sealing and providing strain relief for cable diameters from 2 to 34 mm. The new cable entry system is easy to install. Cable grommets are placed into compartments and are securely fixed to the frame during assembly. The KEL-U-B frame matches exactly the cut-out dimensions of 46 × 46 mm measuring instruments.

Advantages

- Very easy assembly
- Warranty on pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and grommets
- Strain relief according to EN 50262 / 62444
- High stability, vibration proof

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
Protection class	IP54, with gasket and correct selection of cable grommets (certified according to DIN EN 60529:2000-09)
Temperature	- 40°C to + 140°C (static)
Properties	Halogen free, silicone free
Cut-out dimensions	46 × 46 mm / Page 176 - 177
Height KEL	17 mm

Accessories

KT Cable grommets	38 - 42
KEL-SNAP Mounting frames	28 - 29
KEL-EMC Cable collectors	119 - 120
FP Flanged plates	150 - 151


Description

Type

Order No.

Grommets small | large

PU



KEL-U-B4

54204

4|-


10

KEL-U-B4
with V2A screws

54204.200

4|-

10



KEL-U-B1

54206

-|1

10

KEL-U-B1
with V2A screws

54206.200

-|1

10