icotek
NORTH AMERICA

TRIMANTEC

KEL-BES
Brush Frames for Cable Entry

Suitable for electronic enclosure construction ...

... as well as for energy and building technology

Description	Type	Order No.	Cut-out	PU
	KEL-BES 24	51515	36 x 112 mm	10
	KEL-BES 16	51510	36 x 86 mm	10
	KEL-BES 10	51505	36 x 65 mm	10

Product Description

Cable entry frames KEL-BES for routing cables into network enclosures, control boxes and control panels.

KEL-BES is also an ideal solution for entry and exit of cables that are routed inside raised floors, e.g. in computer centers.

The KEL-BES frames match exactly the cut-out dimensions for 10-, 16- or 24-pole standard industrial connectors.

Advantages

- Fast and easy assembly
- Versatile use
- Shielding against dust and drafts
- Thermal protection, separation of cold and warm air
- Visual screenig
- Edge protection

Specifications

Material	**Frame: Polyamide (PA) (Flame class UL94-V0) Brushes: Polyamide (PA) Brush profile: carbon steel, zinc plated**
Temperature	**- 20°C to + 90°C**
Properties	**Halogen free, silicone free**
Height KEL-BES	**10 mm**

Accessories

KEL-EMC-PF Cable collectors   119