KVTSplit Cable Glands



Product Description

KVT is a circular split frame for quick and easy installation and sealing of cables or complete cable harnesses.

Polyamide locknuts are included in the shipment.

For routing D-Sub, DVI or PROFIBUS connectors in combination with the split cable glands KVT, special locknuts with cut-outs are required.

Locknuts

Locknuts with special cut-outs are available separately. The cut-out dimensions are listed on page 158.



KGM-SUB-D9 fits D-Sub 9 connectors (Required wall cut-out: Ø 36 mm, PU: 10)

☐ Order No. 45105 ☐ Order No. 45106

KGM-PB fits DVI and PROFIBUS connectors (Required wall cut-out: Ø 42 mm, PU: 10)

☐ Order No. 45107 ☐ Order No. 45109

KGM-SUB-D25 fits SUB-D25 connectors (Required wall cut-out: Ø 50 mm, PU:10)

☐ Order No. 45108 ☐ Order No. 45110



54 1

up to NEMA



*
45-2 certifi

B RC

Made in Germany



Click to shop online @ www.trimantec.com or call 336-767-1379



Description	Туре	Order No.	Grommets small large	Thread Thread length	PU
Ø 40 □30 ■30 M20x1,5	KVT 20**	□ 45034 ■ 45024	1 -	M20 × 1.5 Length: 14 mm	10
Ø 40 □30 □30 M25x1,5	KVT 25***	□ 45035 ■ 45025	1 -	M25 × 1.5 Length: 14 mm	10
Ø40 □30	KVT 32	□ 45036 ■ 45026	1 -	M32 × 1.5 Length: 14 mm	10
M32x1,5	KVT 32 + KGM-SUB-D9	☐ 45037 ■ 45027	1 -	M32 × 1.5 Length: 14 mm	10
Ø 48 © 29,80	KVT 40	☐ 45203 ■ 45028	1 -	M40 × 1.5 Length: 14 mm	10
* Only valid for gray product types	KVT 40 + KGM-PB	☐ 45205 ■ 45029	1 -	M40 × 1.5 Length: 14 mm	10

^{*} Only valid for gray product type

^{**} Max. cable diameter of 11 mm | *** Max. cable diameter of 15 mm
























Туре	Order No.	Grommets small large	Thread Thread length	PU	Description
KVT 50 2	☐ 45204 ■ 45030	2 -	M50 × 1.5 Length: 14 mm	5	Ø60 53,5
KVT 50 2 + KGM-SUB-D25	☐ 45206 ■ 45031	2 -	M50 × 1.5 Length: 14 mm	5	M50 x 1.5
KVT 63 1	☐ 45212 ☐ 45112	- 1	M63 × 1.5 Length: 14 mm	5	Ø70,50 □52
KVT 63 4	☐ 45215 ■ 45115	4 -	M63 × 1.5 Length: 14 mm	5	M63x1,5
* Only valid for	gray product	types			

KVT Split Cable Glands



Advantages

- Insertion of pre-terminated cables
- Warranty on pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of grommets
- Suitable for standard or metric cut-outs
- Polyamide locknuts are included in the shipment



Specifications

Material

Color	gray (similar RAL 7035)
	■ black
Flame class	UL94-Vo, self-extinguishing
Protection class	IP54, with gasket and correct

Polycarbonate (PC)

selection of the cable grommets (certified according to DIN EN 60529:2000-09)

Temperature - 30°C to + 100°C (static) Properties Halogen free, silicone free Cut-out dimension Metric standard sizes

Accessories

38 - 42 KT Cable grommets KVT-EMC Brackets 121 Locknuts 158