

CUBE20/67 INTERFACE

Cube20/67 system connection



Click to shop online @ www.trimantec.com or call 336-767-1379

Illustration



Product may differ from Image

Approvals



Internal communication

Current consumption max. 25 mA

Cube67 System supply

Cube67 system connection	max. 10 m
I/O capacity	modular Cube20/67 fieldbus station: Cube20 bus node + 15 Cube20/67 modules
Sensor supply US	24 V DC (18...30.2 V DC) EN 61131-2, max. 4 A
Actuator supply UA	24 V DC (18...30.2 V DC) EN 61131-2, max. 4 A

Connections

Fieldbus	M12 (female) 6-pole
Sensor-system/actuator supply	4 × Spring clamp terminals, max. 2.5 mm ² (max. 12 A)
I/O ports	8 × Spring clamp plug-in terminals, max. 2.5 mm ²

The information in this brochure has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 06/17

Murrelektronik GmbH | Falkenstraße 3 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com

General data

Protection	IP20
Mounting method	DIN-rail mountable (EN 60715)
Temperature range	0...+55 °C (storage temperature -20...+85 °C)
Dimensions H x W x D	117x56x47 mm

Diagnostic

Communication status	via LED
----------------------	---------

Commercial data

country of origin	DE
customs tariff number	85176200
EAN	4048879049269
eClass	27242608
minimum order quantity	1