




Type EWT-PA split-flex



Product information

The EWT-PA cable protection conduits are made of specially modified polyamide 6. The material is halogen, phosphor and cadmium-free. The conduits are suitable for static applications involving light to medium mechanical loads.

The EWT-PA cable protection conduits consist of a two-piece slotted conduit system and feature the following advantages:

- Cable protection conduits can be opened and closed at any time.
- Mounting of pre-assembled cables
- Retrofitting or repair in mechanical and plant engineering

Color: Black

Information, conformities and approvals



Article	Order No.	A Ø mm	B Ø mm	R stat. mm	Weight kg/100m	PU m
EWT-PA-M10/P7	83164250	5.7	11.5	70	3.7	50
EWT-PA-M12/P9	83164252	7.9	12.9	75	4.6	50
EWT-PA-M16/P11	83164254	10	16.2	100	6.0	50
EWT-PA-M20/P16	83164256	13.7	21	120	11.0	50
EWT-PA-M25/P21	83164258	19.8	28.4	170	16.6	50
EWT-PA-M32/P29	83164260	25	34.2	180	21.0	25
EWT-PA-M40/P36	83164262	32.3	43.5	200	29.3	25
EWT-PA-M50/P48	83164264	44	53.3	240	40.0	25
EWT-PA-70 Jumbo	83261022	62.2	79	300	53.0	10



Type EWT-PA split-flex

Material properties



mod. polyamide PA 6



High angle consistency >900 N According to IEC EN 61386 M25/P21



Flexural fatigue strength >15000 ~ According to IEC EN 61386

Thermal properties



Temperature / temperature range -40 °C – 120 °C
short termshort term: 160 °C

Fire properties



Fire classification acc. to UL94: HB

Chemical resistance



Resistant to: Alcohol, Mineral oils, Greases, Fuels

Technical information



Halogen-free

Conformity



RoHS (EC Directive 2011/65/EU)

Approvals and operating permits



ECOLAB approval

General information



Made in Germany