




Typ UHE



PRODUCT INFORMATION

The UHE holder is a one-piece conduit holder in which the lid is connected to the holder by a film hinge. It is manufactured from a specially modified Polyamide. The material is halogen, phosphor and cadmium-free. The holder is used to fix cable protection conduits to equipment and machinery.

The UHE holder features the following advantages:

- Quick assembly thanks to single-hole fixing
- Protective conduits only need to be snapped on, which makes them excellent

for overhead installations.

- Optimum connection of conduit to holder thanks to double webs of holder
- Optimised axial strain relief of the corrugated conduit achieved with integrated double webs
- Highest degree of retention power.
- Suitable for all Murrflex corrugated conduit profiles.

Specification:

- EN 45545-2 3x HL3
- ECE 324 R 118 Annex 6+8

SPECIFICATIONS

- mod. polyamide PA 6
- 40 – 110 °C short term 140 °C
- acc. to UL94 V0 self-extinguishing
- C.I.T. R22 / R23 HL3 : 0,49
- LOI R22 / R23 HL3 : ≥ 32 %
- Ds (max.) R22 / R23 HL3 : 137
- Alcohol
- Greases
- Fuels
- Mineral oils



Article	Order No.	Color	UV	G suitable for	A mm	B mm	C mm	PU pcs.
UHE P07 ¹⁾	83621850	Black	✓	M4	17.00	21.50	15.00	100
UHE P09 ¹⁾	83621852	Black	✓	M5	20.50	24.50	15.00	100
UHE P11 ¹⁾	83621854	Black	✓	M5	24.00	27.00	15.00	100
UHE P16 ¹⁾	83621856	Black	✓	M6	30.00	33.00	15.00	100
UHE P21 ¹⁾	83621858	Black	✓	M6	38.50	42.00	15.00	100
UHE P29 ¹⁾	83621860	Black	✓	M6	45.50	48.00	15.00	50
UHE P36 ¹⁾	83621862	Black	✓	M6	55.50	56.00	15.00	50
UHE P48 ¹⁾	83621864	Black	✓	M6	67.50	68.00	15.00	50
UHE P07	83621810	Gray		M4	17.00	21.50	15.00	100
UHE P09	83621812	Gray		M5	20.50	24.50	15.00	100
UHE P11	83621814	Gray		M5	24.00	27.00	15.00	100
UHE P16	83621816	Gray		M6	30.00	33.00	15.00	100
UHE P21	83621818	Gray		M6	38.50	42.00	15.00	100
UHE P29	83621820	Gray		M6	45.50	48.00	15.00	50
UHE P36	83621822	Gray		M6	55.50	56.00	15.00	50
UHE P48	83621824	Gray		M6	67.50	68.00	15.00	50

¹⁾ With ECE 324 R 118 Annex 6+8 approval

Typ UHE

MATERIAL PROPERTIES



Material

mod. polyamide PA 6

THERMAL PROPERTIES



Temperature / temperature range

-40 – 110 °C short term 140 °C

FIRE PROPERTIES



Fire classification

acc. to UL94 V0 self-extinguishing



Fire properties as per EN 45545-2

C.I.T. R22 / R23 HL3 : 0,49

LOI R22 / R23 HL3 : ≥ 32 %

Ds (max.) R22 / R23 HL3 : 137

CHEMICAL RESISTANCE



Resistant to:

Alcohol

Greases

Fuels

Mineral oils

TECHNICAL INFORMATION



Halogen-free

CONFORMITY



RoHS (EC Directive 2011/65/EU)

APPROVALS AND OPERATING PERMITS



EU railway approval

EN 45545-2 R22/R23 3x HL3

GENERAL INFORMATION



Made in Germany

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

© Murrplastik Systemtechnik GmbH • prod_125932~20220928~890283~suv_uh_e