










Click to shop online @ www.trimantec.com or call 336-767-1379



KEL-DP also available in black.



KEL-DP-E Cable Entry Plates

Type	Order No.	Cut-out [mm]	Number of cables	PU	Description
KEL-DP-E 46 7	<input type="checkbox"/> 43585 <input checked="" type="checkbox"/> 50585	46 x 18	5x max. 8.3 mm 2x max. 6.5 mm	10	
KEL-DP-E 46 9	<input type="checkbox"/> 43587 <input checked="" type="checkbox"/> 50587	46 x 18	8x max. 6.5 mm 1x max. 12.1 mm	10	
KEL-DP-E 86 13	<input type="checkbox"/> 43581 <input checked="" type="checkbox"/> 50581	86 x 18	11x max. 8.3 mm 2x max. 6.5 mm	10	
KEL-DP-E 86 17	<input type="checkbox"/> 43583 <input checked="" type="checkbox"/> 50583	86 x 18	16x max. 6.5 mm 1x max. 12.1 mm	10	
KEL-DP-E 112 16	<input type="checkbox"/> 43576 <input checked="" type="checkbox"/> 50576	112 x 18	4x max. 6.5 mm 11x max. 8.3 mm 1x max. 12.1 mm	10	
KEL-DP-E 112 21	<input type="checkbox"/> 43578 <input checked="" type="checkbox"/> 50578	112 x 18	16x max. 6.5 mm 4x max. 8.3 mm 1x max. 12.1 mm	10	
KEL-DP-S 69 8	<input type="checkbox"/> 43591 <input checked="" type="checkbox"/> 50591	69 x 10 Edge radii Rz	8x max. 7.5 mm	10	

* Only valid for gray product types

Product Description

KEL-DP-E entry plates are designed for routing standard cables (without connectors). The KEL-DP products are a cost saving alternative to traditional cable glands.

Simply put a small slit in the thin membrane, push standard cables through and it's immediately sealed (IP64 / up to NEMA 12).

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

A special fixing rib ensures a centered fit in the cut-outs.

Advantages

- Quick and easy assembly, no tools required
- High packing density
- Cost-effective
- Hygienic design
 - free of dirt-collecting recesses
- For wall thickness 1.5 - 2.5 mm

Specifications

Material	Elastomer
Color	<input type="checkbox"/> gray (similar RAL 7035) <input checked="" type="checkbox"/> black
Flame class	UL94-V0, self-extinguishing
Protection class	IP64 (certified according to DIN EN 60529:2000-09)
Temperature Properties	- 40°C to + 90°C (static)
Height	Halogen free, silicone free 5 mm

Accessories

ST-B Plugs 74