

# KEL-DPZ-B

## Cable Entry Plates



Click to shop online @ [www.trimantec.com](http://www.trimantec.com) or call 336-767-1379



**IP66**



KEL-DPZ also available in black.



KEL-DPZ-B on request also available with threaded bushings.



Membrane on front

### Product Description

The KEL-DPZ-B entry plates are designed for routing standard cables (without connectors).

The assembly of the KEL-DPZ-B with cables or pneumatic hoses can be done within seconds. Simply put a small slit in the thin membrane, push standard cables through and it's immediately sealed (IP66/NEMA 12) and strain relieved.

With an area of only 46 × 46 mm, up to 25 cables can be easily routed and sealed according to IP66.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

### Advantages




- Space saving shape
- Dual sealing of cables according to IP66
- High packing density
- Assembly within seconds
- Hygienic design - free of dirt-collecting recesses

### Specifications

Material	Frame: Polyamide (PA) Sealing plate: Elastomer
Color	■ gray (similar RAL 7035) ■ black
Flame class	UL94-Vo, self-extinguishing
Protection class	IP66 (certified according to DIN EN 60529:2000-09)
Temperature Properties	- 40°C to + 90°C (static) Halogen free, silicone free
Cut-out dimensions	46 × 46 mm
Height	10 mm

### Accessories

ST-B Plugs	74
FP Flanged plates	148 - 153

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-B 13	<input type="checkbox"/> 43794 <input checked="" type="checkbox"/> 50794	8× 3.2 - 6.5 mm 4× 5 - 10.2 mm 1× 16 - 22 mm	10
	KEL-DPZ-B 17	<input type="checkbox"/> 43796 <input checked="" type="checkbox"/> 50796	10× 3.2 - 6.5 mm 4× 5 - 10.2 mm 2× 7.5 - 12 mm 1× 9 - 16.2 mm	10
	KEL-DPZ-B 25	<input type="checkbox"/> 43798 <input checked="" type="checkbox"/> 50798	25× 3.2 - 6.5 mm	10

\* Only valid for gray product types