

Electric walk-behind trowels

Electric Walk-behind Trowels



**WACKER
NEUSON**
all it takes!



The emission-free alternative: The CT range of trowels:

Especially in enclosed spaces, working with electric trowels much more comfortable: No harmful exhaust fumes and reduced noise. That makes the CT range very user-friendly and also extremely productive and precise finishing. That is due to the 3-phase electric motor, the balanced design with optimal weight distribution and the robust device concept.

- Low maintenance
- Convenient low weight for comfortable operation
- Emission-free, thanks to the 3-phase electric motor
- Very quiet operation
- Available in 2 sizes of finishing diameter

Electric walk-behind trowels Technical specifications

	CT 24-230E	CT 36-400E
L x W x H mm	1546 x 610 x 1041	2005 x 915 x 1040
Operating weight incl. handle kg	74	104
Troweling diameter mm	610	915
Quantity of blades	4	4
Dimensions Finishing blades mm	229 x 121	
Diameter Float pan mm	603	
RPM rpm	116	50 - 100
Pitch range °	0 - 15	0 - 30
Engine / Motor	Electric	Electric
RPM / speed rpm	2,870	
Engine performance low / high kW	- / 2.2	2.6 / 3.1
Engine RPM low / high rpm	- / 2870	1400 / 2850
Voltage V	230	400
Frequency Hz	50	50
Rated current A	14	5.5 / 7.3

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2019 Wacker Neuson SE.