



Ecocoat Water repellent is a water based water repellent based on the latest nano-technology, that can be used on all mineral surfaces on walls, roofs and paving slabs. Ecocoat is a special chemical composition that reacts with mineral groups and actively bond to mineral surfaces such as concrete and protect against rain, dirt, algae, pollution, oil and others.

Ecocoat Water Repellent is recommended for surfaces like concrete, clay, terracotta and slate etc.

Apply directly on surfaces less than one year old. Older surfaces must first be cleaned thoroughly with a pressure washer before treatment. Surfaces with strong discoloration, algae or moss growth (as well as heavily soiled surfaces) should be treated with Ecocoat CLEANER and finally rinsed with water before treatment.

Preparation: The surface needs to be dry, clean and free from contamination.

Application: Use low-pressure pump, sprayer, brush or roller. A minimum temperature of 5 °C is needed.

Recommendation: Always make a test coat to ensure the compatibility of the product and surface.

Coverage rate: 150-200 ml per m² depending on porosity

Equipment care: Cleaned up in water directly after use.

Storage: Dry and frost-free. Keep out of reach of children.

Package sizes: 25 litres.

Colour: Colourless when applied.

Thinning: Undiluted.

Drying time: Approx. 1 hour at 20° C and 60% RH.

PROPERTIES

Based on the latest technology

Scientifically engineered to protect mineral surfaces by active binding

Specifically designed for concrete, clay roof tiles, brick walls and mineral surfaces

Extremely water repellent and self-cleaning

Obstructs discoloration and prevents salt efflorescence.

Prevents growth of moss, algae and lichens

