

RENOTEC Primer is a special water-based primer for RENOTEC roof coatings with solidifying effect and high penetration depth. It is diffusively and adherent and only suitable for porous surfaces.

Recommended for

All mineral roof tiles, e.g. concrete, clay, slate and fiber cement.

Preparation

Complete roof cleaning with high pressure is necessary to eliminate organic components such as mold, algae or moss, stains, etc.

Application

Use an airless sprayer or sprayer. A minimum temperature of 5 °C is required.

Airless nozzle site: 0,011 – 0,013 inch

Spraying angle: 50°

Pressure: 150 bars

The primer must be completely absorbed. Ensure that after drying no glossy film exists. Low absorbent surfaces such as clay or fiber-cement panels need to be primed thinly. For very porous substrates RENOTEC Primer may be diluted 1: 1 with water. RENOTEC Primer is not suitable for non-porous substrates.

Note: Components that don't need to be treated have to be protected from splashes - eg by covering - as dried RENOTEC Primer is very difficult to remove. Once the primer is dry, RENOTEC roof coating can be applied.

Colour

milky white

Coverage rate

150-200 ml per m², depending on porosity.

Drying time

3 – 5 hours at 20° C and 65% RH. Lower temperatures and higher humidity extend the drying time accordingly.

Packing size

10 Litre Pots (52 Pots per pallet)

Equipment care

Cleaned up in water directly after use.

Storage

Protect from direct sunlight, heat sources and frost. Keep opened container tightly sealed.

Shelf life

12 months (in original sealed container).

Safety and regulations

In accordance with current labelling non-hazardous content. More information regarding precautions can be found on the product label or on the manufacturer's safety data sheet.

