



# Black Jack®

Quality products since 1913



## PERMANENT POTHOLE PATCH



**INSTANT  
DRIVEABILITY**  
Listo para el tráfico



**ALL-WEATHER**  
Para todo tipo de clima

- Use for driveways, parking lots, streets, seaports, railroads
- Use with concrete, brick, asphalt and wood



Ready Road Repair  
6431-9-50



Ready Road Repair  
6431-9-27

**Ready Road Repair®**, the original permanent pothole repair, delivers a zero VOC, permanent, all-weather repair to asphalt, concrete, brick and wood. Use **Ready Road Repair®** in any weather conditions, year round to repair parking lots, streets, driveways, seaports, and railroads. **Ready Road Repair®** complies with Army Corp. of Engineers Specifications.



# 6431

## Ready Road Repair

### Permanent Pothole Patch

- Permanent
- All-Weather
- Immediately ready for traffic
- Complies with Army Corp. of Engineers Specifications
- Use for driveways, parking lots, streets, seaports, railroads
- Use with concrete, brick, asphalt and wood



**READY ROAD REPAIR** is a premium repair for holes in roadways, bridges, parking lots or driveways. This product is a blend of stones and asphalt designed to fill larger holes (4" or more) and depressions to make a permanent repair. After product is installed it is available for immediate use. Can be applied year round.

**PREPARATION:** RRR should be stored in protected areas and kept below 100 °F. In colder climates it is best to store RRR in a heated area (72 °F or higher) several hours prior to use. This will make the product much easier to work with. RRR can be used under any weather conditions: wet, dry, cold, etc.

**APPLICATION:** 1. (No priming or cutting is necessary.) Sweep water, dust and loose material from hole. 2. Place enough RRR to slightly overfill hole. 3. Compact with tamper. You can also place a flat piece of plywood over repair and then drive over it to compact it into the hole. Repair is ready for traffic immediately after compaction.

#### 6431-9-27 - PAIL

**COVERAGE RATE:** 40 lbs./18.1 kg : One container of material will cover approximately 4 - 4.5 sq.ft. at 1" thickness.

**PRECAUTIONS:** Use of gloves is recommended. Clean tools with Black Jack Asphalt and Tar Remover. Traffic improves compaction. A sealcoat is not required, but may be applied approximately 180 days after the product fully cures. Due to no solvents in this product, the patch will dry slower, and should not be sealcoated before 6 months. Keep sealed when not in use. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not allow stored product to freeze.

#### 6431-9-50 - BAG

**COVERAGE RATE:** 50 lbs./22.7 kg : One 50 lb. bag of material will cover approximately 5.6 sq.ft. at 1" thickness.

**PRECAUTIONS:** Use of gloves is recommended. Clean tools with mineral spirits. A sealcoat is not required, but may be applied approximately 180 days after the product fully cures. Traffic improves compaction. Keep sealed when not in use. When transporting this product, ensure that bag is closed, stable and flat. Do not allow bag to tumble as this may cause bag to open and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not allow stored product to freeze. Do not use in drinking water or food systems.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
6431-9-27	40 lbs.	13" x 13" x 12"	40 lbs./18.1 kg	40 lbs.	1	027134643132
6431-9-50	50 lbs.	24.6" x 15.74" x 3.543"	50 lbs./22.7 kg	50 lbs.	1	027134643101

**www.gardner-gibson.com**  
**Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449**  
**Phone: (813) 248-2101**